novatio

TECHNICAL DATA SHEET



Skincoat Ramen en Deuren

WAX FOR MAXIMUM PROTECTON

- Against corrosion and rust.
- Ideal after welding, drilling.
- Resistant after rapid drying.

Technical Info

- · Composition: wax base dissolved in solvent.
- Colour: brown.
- · Odour: typical wax/solvent scent.
- pH: insoluble in water, neutral.
- Flash point: active agent: > 45 °C.
- During processing: highly flammable.
- Relative density: 0.6576 kg/dm³.
- Drying time: depending on relative humidity and ambient temperature, 15 to 30 minutes.
- Consumption per 500 ml approx. 4 to 6 m² at a thickness of 100 microns.
- Shelf life: 12 months, dry, cool and frost-free.
- Safety measures: please consult the safety data sheet.

Packing

Skincoat Ramen en Deuren - aerosol 500ml

Use

- · After releasing the mixing ball, shake well before use.
- Apply and allow to dry.
- After use, empty the head with can upside down. Edge contamination can be cleaned with Safety Clean.

118001116

Product [SCT R&D]

Characteristics

Highly adhesive wax, durable resistance to water, weather effects and salts. Safe on plastics, paints and rubbers. With extension hose for hollow spaces.



Novatio is a registered trademark of Novatech International nv. Industrielaan 5B - B-2250 Olen - Belgium | Tel: +32 14 25 67 40 | info@novatio.be

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV