



PUP-002 PUC Primer Synthetics

Surface Protection & Treatment

1K ADHESIVE PRIMER

- ✓ For PUC-001 2K PU Coating.
- ✓ On varnish and plastic.
- ✓ 1K polymer.
- ✓ Brief drying time.

Technical Info

- Basis: 1K polymer.
- Colour: transparent.
- Odour: characteristic.
- Processing temperature: from +10°C to +40°C.
- Relative air humidity during use: max. 80%
- Dry film thickness: 3-5 µm.
- Waiting time (between layers): 2-3 minutes.
- Dry to the touch: 5-10 minutes.
- Can be varnished/sanded: 10 minutes.
- Shelf life: 24 months, in dry, cool and frost-free place.
- Safety measures: please refer to the safety data sheet.

Packing

PUP-002 PUC Primer Synthetics - aerosol 400ml 140120000

Product [PUP-002]

Characteristics

PUP-002 PUC Primer Synthetics ensures excellent adhesion of PUC-001 2K PU Coating Black on plastics, such as PVC, ABS, PU, PS, PC, PBT, PET ..., powder coatings and varnishes. Pre-sanding is not necessary, making application quick and easy.

Use

- Apply to a clean, dry and stable substrate. If necessary, clean with Safety Clean and/or Multifoam beforehand.
 - Shake well for two minutes and apply to a test piece.
 - Apply a thin, uniform layer of 20 to 30 cm.
 - Allow gas to evaporate briefly and apply a second thin layer.
 - Empty the nozzle spraying with the can upside down.
- In case of doubt, test adhesion. Adhesion to PP, PE, PTFE, etc. is not good. A white bloom may appear on transparent plastics, such as Polycarbonate (PC) or Plexiglas (PMMA).