



Maintenance Spray H1

FAST AND MULTIFUNCTIONAL OIL

- ✓ High penetration capacity
- ✓ Cleans, lubricates, protects and repels water
- ✓ Dissolves rust and releases bolts and nuts



Technical Info

- NSF registration number: Category H1. Compliant with: FDA, Titel 21, Sektion 178.3570.
- Free of: lead, animal fat and synthetic oils.
- Odour: typical.
- Operating temperature: -15°C to +110°C.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Maintenance Spray H1 - aerosol 400ml

232501000

Product [MS1]

Characteristics

Combines rapid penetrating and water displacement capacities, for use in all food processing areas. It will also leave a protective film offering a short term corrosion protection. Free from lead, animal fats and synthetic oils. Operating temperature of finished film: -15°C to +110°C.

Applications

Suitable for all food processing companies and firms which develop machinery that may come in contact with food:

- all food companies
- abattoirs
- dairy factories
- bakeries
- canneries
- breweries
- bottle manufacturing plants
- cardboard factories
- stops and prevents short circuits
- loosens rusted nuts, bolts, screws, valves, flaps and moving parts
- cleans electrical and non-electrical contacts
- protects printed circuit boards, electrical contacts, sensors, switches, ... against moisture
- gets RVS and chromium components shiny again
- removes oil and tar stains
- repels moisture from switchboxes and electronic measuring equipment
- detaches tar and old greases
- protects and creates a shine on uncoated and painted metal components
- keeps handles, guides and machine rods in good operating condition
- protects tools and machines

Use

- Shake before use.
- Spray application.
- Use the straw for less accessible places.