

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

NOVALUBE CERAMIC AEROSOL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : NOVALUBE CERAMIC AEROSOL
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Lubricant

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
✉ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
✉ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

2.2. Label elements



Signal word

Danger

H-statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

NOVALUBE CERAMIC AEROSOL

P280	Wear protective gloves, protective clothing and eye protection/face protection.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
propane 01-2119486944-21	74-98-6 200-827-9	25% ≤C≤50%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
butane 01-2119474691-32	106-97-8 203-448-7	25% ≤C≤50%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
naphtha (petroleum), hydrotreated light 01-2119475133-43	64742-49-0 265-151-9	10% ≤C≤18%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)(6)	Constituent	
calcium dihydroxide 01-2119475151-45	1305-62-0 215-137-3	C<3%	Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335	(1)(2)	Constituent	
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C≤1.1%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	

- (1) For H- and EUH-statements in full: see section 16
(2) Substance with a Community workplace exposure limit
(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006
(21) 1,3-butadiene <0.1%

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Irritation of the nasal mucous membranes.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

2 / 18

NOVALUBE CERAMIC AEROSOL

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: seal off low-lying areas. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Dam up the liquid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers.

Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Store in a cool area. Keep out of direct sunlight. Fireproof storeroom. Keep container in a well-ventilated place.

7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

NOVALUBE CERAMIC AEROSOL

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Calcium dihydroxide	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1 mg/m ³ (2)
	Short time value (Indicative occupational exposure limit value)	4 mg/m ³ (2)

(2): Respirable fraction

Belgium

Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m ³
	Short time value	400 ppm
	Short time value	1000 mg/m ³
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m ³
Calcium (dihydroxyde de) (fraction alvéolaire)	Time-weighted average exposure limit 8 h	1 mg/m ³
	Short time value	4 mg/m ³
Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m ³
	Short time value	10 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

The Netherlands

Calcium-dihydroxide	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	0.33 ppm (1)
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1 mg/m ³ (1)
	Short time value (Public occupational exposure limit value)	1.3 ppm (1)
	Short time value (Public occupational exposure limit value)	4 mg/m ³ (1)
Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m ³

(1) respirabel

France

Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m ³
Calcium (hydroxyde de) fraction alvéolaire	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1 mg/m ³
	Short time value (VRI: Valeur réglementaire indicative)	4 mg/m ³
n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m ³

Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³ (1)
Calciumdihydroxid	Time-weighted average exposure limit 8 h (TRGS 900)	1 mg/m ³ (2)
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³ (1)
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm (3)
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m ³ (3)

(1) UF: 4 (II)

(2) Einatembare Fraktion; UF: 2 (I)

(3) UF: 2 (II)

NOVALUBE CERAMIC AEROSOL

Austria

2-Propanol Kurzzeitwert für Großguss	*) Kurzzeitwert für Großguss gilt bis 31.12.2013	
	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	2000 mg/m ³
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m ³
Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m ³
Calciumdihydroxid	Tagesmittelwert (MAK)	1 mg/m ³ (1)
	Kurzzeitwert 5(Mow) 8x (MAK)	4 mg/m ³ (1)
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m ³

(1) Einatembare Fraktion

UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m ³
Calcium hydroxide (Respirable fraction)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	4 mg/m ³
Calcium hydroxide	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	5 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m ³

USA (TLV-ACGIH)

2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
	Explosion hazard	
Calcium hydroxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m ³
Mineral oil, excluding metal working fluids: Pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m ³ (1)
Propane	See Appendix F: Minimal Oxygen Content; Simple asphyxiant, Explosion hazard	

(1) (I): Inhalable fraction

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific
----------------------	--	---------	-------------------------

8.1.2 Sampling methods

Product name	Test	Number
Calciumdihydroxide	NIOSH	7020
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

5 / 18

NOVALUBE CERAMIC AEROSOL

Product name	Test	Number
Isopropyl Alcohol	NIOSH	3900
Isopropyl Alcohol	OSHA	5001
Oil Mist (Mineral)	NIOSH	5026

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

naphtha (petroleum), hydrotreated light

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects inhalation	1286.4 mg/m ³	
	Long-term local effects inhalation	837.5 mg/m ³	
	Acute local effects inhalation	1066.67 mg/m ³	

calcium dihydroxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	1 mg/m ³	
	Acute local effects inhalation	4 mg/m ³	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m ³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

DNEL/DMEL - General population

naphtha (petroleum), hydrotreated light

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects inhalation	1152 mg/m ³	
	Long-term local effects inhalation	178.57 mg/m ³	
	Acute local effects inhalation	640 mg/m ³	

calcium dihydroxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	1 mg/m ³	
	Acute local effects inhalation	4 mg/m ³	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m ³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

PNEC

calcium dihydroxide

Compartment	Value	Remark
Fresh water	0.49 mg/l	
Fresh water (intermittent releases)	0.49 mg/l	
Marine water	0.32 mg/l	
STP	3 mg/l	
Soil	1080 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.4 mm	Class 6	
butyl/viton	> 480 minutes		Class 6	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Head/neck protection. Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

6 / 18

NOVALUBE CERAMIC AEROSOL

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Colour	White
Odour	Solvent-like odour
Odour threshold	No data available in the literature
Melting point	Not applicable (aerosol)
Boiling point	No data available in the literature
Flammability	Extremely flammable aerosol.
Explosion limits	0.6 - ... vol %
Flash point	Not applicable (aerosol)
Auto-ignition temperature	No data available in the literature
Decomposition temperature	No data available in the literature
pH	Not applicable (non-soluble in water)
Kinematic viscosity	Not applicable (aerosol)
Solubility	Water ; insoluble
Log Kow	Not applicable (mixture)
Vapour pressure	3500 hPa ; Propellant
Absolute density	1400 kg/m ³ ; 20 °C
Relative density	1.40 ; 20 °C ; Calculated
Relative vapour density	> 1
Particle size	Not applicable (liquid)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5.61 mg/l air	4 h	Rat (male / female)	Read-across	

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

7 / 18

NOVALUBE CERAMIC AEROSOL

calcium dihydroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 425	> 2000 mg/kg bw		Rat (female)	Experimental value	
Dermal	LD50	OECD 402	> 2500 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (dust)	LC50	OECD 436	> 6.04 mg/l	4 h	Rat (male / female)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Irritating	OECD 404	4 h	1; 24; 48; 72; 168 hours	Rabbit	Read-across	
Inhalation (vapours)	Not irritating		1 h		Human	Experimental value	

calcium dihydroxide

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	OECD 405	1 h	1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Inhalation	Irritating; STOT SE cat.3					Literature study	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

Conclusion

Causes skin irritation.

Causes serious eye irritation.

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406	6 h	24; 48 hours	Guinea pig (male)	Read-across	

calcium dihydroxide

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value	

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

8 / 18

NOVALUBE CERAMIC AEROSOL

propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOEL	Subacute toxicity test	< 500 mg/kg bw/day	Kidney	No effect	4 weeks (5 days / week)	Rat (male)	Read-across
Dermal	NOAEL	Equivalent to OECD 453	0.5 ml		No effect		Mouse (male / female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	1402 mg/m ³ air	General	No effect	107 weeks (6h / day, 5 days / week) - 109 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

calcium dihydroxide

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 422	1000 mg/kg bw/day		No effect		Rat (male / female)	Experimental value
Dermal								Data waiving
Inhalation (dust)	NOAEC	OECD 412	0.107 mg/l		No effect	2 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm		No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male / female)	Experimental value

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

calcium dihydroxide

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 473	Human lymphocytes		Experimental value	

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

9 / 18

NOVALUBE CERAMIC AEROSOL

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

Mutagenicity (in vivo)

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation)	EPA OPPTS 870.5395	4 weeks (6h / day, 5 days / week)	Rat (male / female)		Read-across

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	Dose level	Equivalent to OECD 451	9869 mg/m ³	113 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Read-across
Dermal	NOAEL	Equivalent to OECD 451	0.05 ml	102 weeks (3 times / week)	Mouse (male)	No carcinogenic effect		Experimental value

calcium dihydroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	2150 mg/kg bw/day - 2280 mg/kg bw/day	104 week(s)	Rat (male / female)	No carcinogenic effect		Read-across

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	23900 mg/m ³ air	14 days (6h / day)	Rat	No effect	Foetus	Read-across
Maternal toxicity (Dermal)	NOAEL	Equivalent to OECD 414	23900 mg/m ³ air	14 day(s)	Rat	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC (P/F1)	Equivalent to OECD 416	≥ 20000 mg/m ³ air	10 weeks (6h / day, 7 days / week)	Rat (male / female)	No effect		Experimental value

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

10 / 18

NOVALUBE CERAMIC AEROSOL

calcium dihydroxide

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	≥ 440 mg/kg bw/day	10 days (gestation, daily)	Mouse	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	≥ 440 mg/kg bw/day	10 days (gestation, daily)	Mouse	No effect		Read-across
Effects on fertility (Oral (stomach tube))	NOEL	OECD 422	1000 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Chronic effects from short and long-term exposure

NOVALUBE CERAMIC AEROSOL

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

NOVALUBE CERAMIC AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

naphtha (petroleum), hydrotreated light

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	10 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	4.5 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	3.1 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity fish	NOELR	OECD 204	2.6 mg/l	14 day(s)	Pimephales promelas	Semi-static system	Fresh water	Experimental value; Reproduction
Long-term toxicity aquatic crustacea	NOELR	OECD 211	2.6 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

11 / 18

NOVALUBE CERAMIC AEROSOL

calcium dihydroxide

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	50.6 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	OECD 202	49.1 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Estimated value
Toxicity algae and other aquatic plants	ErC50	OECD 201	184.57 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	48 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC		32 mg/l	14 day(s)	Crangon sp.	Semi-static system	Salt water	Experimental value; Growth
Toxicity aquatic micro-organisms	EC50	OECD 209	300.4 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; Respiration

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish	NOELR	Petrotox computer model	> 1000 mg/l	28 day(s)	Brachydanio rerio			Estimated value
Long-term toxicity aquatic crustacea	NOEC		141 mg/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

Conclusion

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

naphtha (petroleum), hydrotreated light

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	77.05 %; Oxygen consumption	28 day(s)	Experimental value

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	17.668 h	1.5E6 /cm ³	Calculated value

Conclusion

Water

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

NOVALUBE CERAMIC AEROSOL

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

NOVALUBE CERAMIC AEROSOL

naphtha (petroleum), hydrotreated light

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		12.6 - 223.87; Calculated value		Pimephales promelas	Read-across

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.4 - 5.7	23 °C	Experimental value

calcium dihydroxide

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

propan-2-ol

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	1015			Estimated value

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

naphtha (petroleum), hydrotreated light

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	2.380	Calculated value

propan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.185 - 0.541	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

NOVALUBE CERAMIC AEROSOL

Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Groundwater

Groundwater pollutant

naphtha (petroleum), hydrotreated light

Groundwater

Groundwater pollutant

calcium dihydroxide

Water ecotoxicity pH

pH shift

propan-2-ol

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

13 / 18

NOVALUBE CERAMIC AEROSOL

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Rail (RID)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Inland waterways (ADN)

14.1. UN number/ID number

UN number/ID number	1950
---------------------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Class	2
Classification code	5F

14.4. Packing group

Packing group	
---------------	--

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

14 / 18

NOVALUBE CERAMIC AEROSOL

Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number/ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
61 % - 86 %	
854 g/l - 1204 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

15 / 18

NOVALUBE CERAMIC AEROSOL

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· naphtha (petroleum), hydrotreated light · propan-2-ol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· naphtha (petroleum), hydrotreated light · propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· naphtha (petroleum), hydrotreated light · propan-2-ol	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

16 / 18

NOVALUBE CERAMIC AEROSOL

and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

National legislation Belgium

NOVALUBE CERAMIC AEROSOL

No data available

propan-2-ol

Agents cancérogènes, mutagènes et reprotoxiques et aux agents possédant des propriétés perturbant le système endocrinien (Code du bien-être au travail, Livre VI, titre 2)	alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à l'acide fort dans la fabrication d'alcool isopropylique.
--	---

National legislation The Netherlands

NOVALUBE CERAMIC AEROSOL

Waterbezwaarlijkheid	A (3); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

National legislation France

NOVALUBE CERAMIC AEROSOL

No data available

National legislation Germany

NOVALUBE CERAMIC AEROSOL

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	3; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
naphtha (petroleum), hydrotreated light	
TA-Luft	5.2.5/I
calcium dihydroxide	
TA-Luft	5.2.1
TRGS900 - Risiko der Fruchtschädigung	Calciumdihydroxid; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
propan-2-ol	
TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation Austria

NOVALUBE CERAMIC AEROSOL

No data available

National legislation United Kingdom

NOVALUBE CERAMIC AEROSOL

No data available

Other relevant data

NOVALUBE CERAMIC AEROSOL

No data available

naphtha (petroleum), hydrotreated light

TLV - Carcinogen	Mineral oil, excluding metal working fluids: Pure, highly and severely refined; A4
propan-2-ol	
IARC - classification	3; Isopropanol
TLV - Carcinogen	2-propanol; A4

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Reason for revision: 8, 15

Publication date: 2010-07-15

Date of revision: 2023-10-17

Revision number: 0401

BIG number: 49122

17 / 18

NOVALUBE CERAMIC AEROSOL

H412 Harmful to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.