



# Novatex Tape HD

TOP OF THE RANGE TEXTILE TAPE

- ✓ Weather and water resistant.
- ✓ Direct pulling power, also on raw materials.
- ✓ Temperature and tear resistant.

## Technical Info

- Adhesive type: hotmelt / synthetic rubber.
- Total thickness: 0.26 mm.
- Adhesion to steel: 30 N/25 mm.
- Adhesion to PE: 24 N/25mm.
- Adhesion to stone at 0°C: 30 N/25 mm.
- Adhesion to stone at 23°C: 27 N/25 mm.
- Tear strength: 110 N/25 mm.
- Solvent-free.
- Application temperature: from -25°C to +60°C.
- Temperature resistance: -15°C to +50°C.
- Shelf life: 36 months, keep dry, cool and frost-proof.

## Packing

Novatex Tape HD grey - roll 50mm / 50m	561128000
Novatex Tape HD grey - roll 50mm / 10m	561127390

## Product [NTX HD]

### Characteristics

Novatex Tape HD is a superior textile tape in the Novatex line that easily withstands ageing. This HD version has an extremely soft glue coat that allows adhesion to difficult surfaces, such as carpets and even on stone and concrete. The synthetic rubber glue is furthermore temperature resistant. The top layer of Novatex Tape HD consists of weather and water resistant PE-coated and tear-resistant textile.

### Applications

Novatex Tape HD has a high level of immediate adhesive power on rough surfaces, such as stone, concrete, brick, etc., but also on carpets and even on difficult plastics such as polyethylene.

Novatex Tape HD can also be used at extremely low temperatures down to -25°C.