

Multispray Windows and Doors

Lubricants

LUBRICANT FOR WINDOW AND DOOR HARDWARE

- Lubricates, protects and displaces moisture
- Temperature-resistant from -80°C to +190°C
- Colourless and silicone-free
- Safe for plastics, metal, rubber and painted surfaces

Technical Info

- Base: Mineral oil.
- Colour: Colourless.
- Odour: Characteristic.
- Water solubility: Insoluble.
- Vapour pressure: 8.53 bar.
- Boiling point: 187°C to 300°C.
- Relative density (at 20°C): 0.81 g/cm³.
- Temperature resistance: -80°C to +190°C.
- Dynamic viscosity (at 20°C): 1 mPa·s.
- Kinematic viscosity (at 20°C): 1 mm²/s.
- Packaging: 500 ml aerosol.
- Shelf life: 48 months.
- Safety precautions: Refer to the latest version of the Safety Data Sheet available on the website.

Packing

Multispray Windows and Doors - aerosol 500ml	236115116

Product [MUS R&D]

Characteristics

- Multispray Windows and Doors combines penetrating action, lubrication, protection, cleaning, rust prevention and moisture displacement.
- Silicone-free and safe for plastics, metal, rubber and painted surfaces.
- PTFE-free.

Applications

- Hinges
- Window and door hardware
- Tilt-and-turn systems
- Cylinder locks and door locks
- Multipoint locking systems and locking mechanisms
- Rails and guides

Use

- Shake well before use.
- Spray onto the surface and allow to penetrate.

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV.