



Silicon Repair Tape

Tapes

SUPER-POWERFUL SELFVULCANISING TAPE

- Pressure and heat resistant.
- Insulating capacity up to 8000 volts.
- Timeless liquid and airtight.
- Instant vulcanization, even under water.

Technical Info

- Thickness: 0,5 mm.
- Width: 25 mm.
- · Length: 3 m.
- Pressure resistance: up to 15 bar.
- Temperature resistance: -65°C to 260°C.
- Elasticity: 300%.
- Shelf life: 36 months, keep dry, cool and frost-proof.

Packing

Silicon Repair Tape black - roll 25mm / 3m	565525000
Silicon Repair Tape transparent - roll 25mm / 3m	565515000

Product [SRT]

Characteristics

This silicone tape can be used as insulation, sealing or repair tape under varying conditions. It can be applied in poor conditions, where preparation is difficult, because it bonds by itself. The surface therefore does not necessarily have to be cleaned and dried. Remains flexible and resists petroleum (gasoline), oil, acids, solvents, salt water, road salt and UV light. Available in black or transparent, depending on application.

Applications

Repairing leaking hoses, sealing pipes and fittings, insulating electrical wires, corrosion protection, sealing connectors and fittings, protecting rigging and rope ends, marking lines and chains, giving anti-slip qualities to handles and tools,....

Use

Stretching the tape and wrapping it tightly (half-overlapped) around itself creates a permanent bond almost immediately.



Novatio is a registered trademark of Novatech International nv. Industrielaan 5B - B-2250 Olen - Belgium | Tel: +32 14 85 97 37 | info@novatio.be

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV