

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



SOLVETRON AEROSOL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SOLVETRON AEROSOL
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Degreasing agent
Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements



Contains: hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; hydrocarbons, C6, isoalkanes, < 5% n-hexane; propan-2-ol.

Signal word Danger

H-statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 3.2, 8, 9, 15

Revision number: 0900

Publication date: 2001-02-13

Date of revision: 2021-10-20

BIG number: 33450

1 / 25

878-16239-027-en

SOLVETRON AEROSOL

P-statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves, protective clothing and eye protection/face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 01-2119475515-33	927-510-4	C≤40%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent	
hydrocarbons, C6, isoalkanes, < 5% n-hexane 01-2119484651-34	931-254-9	C≤30%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent	
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C≤20%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
acetone 01-2119471330-49	67-64-1 200-662-2	C≤10%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
propane 01-2119486944-21	74-98-6 200-827-9	C≤5%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
carbon dioxide	124-38-9 204-696-9	C≤3%	Press. Gas - Liquefied gas; H280	(1)(2)(l)	Propellant	
n-hexane 01-2119480412-44	110-54-3 203-777-6	C≤2%	Flam. Liq. 2; H225 Repr. 2; H361f Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411 STOT RE 2; H373: C≥5%, (CLP Annex VI (ATP 0))	(1)(2)(10)	Constituent	
cyclohexane 01-2119463273-41	110-82-7 203-806-2	C≤0.4%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(10)	Constituent	M: 1 (Acute, ECHA)

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(l) Exempted from registration under REACH according to Annex IV (Regulation (EC) No 1907/2006)

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

2 / 25

SOLVETRON AEROSOL

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dizziness. Drowsiness.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. If exposed to fire cool the closed containers by spraying with water. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SOLVETRON AEROSOL

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight. Keep container tightly closed.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m ³
Carbon dioxide	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	5000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	9000 mg/m ³
Cyclohexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	700 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	72 mg/m ³

Belgium

SOLVETRON AEROSOL

Acétone <i>shall apply from 2022-01-01</i>	Time-weighted average exposure limit 8 h	246 ppm
Acétone <i>shall apply until 2021-12-31</i>	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1210 mg/m ³
Acétone <i>shall apply from 2022-01-01</i>	Time-weighted average exposure limit 8 h	594 mg/m ³
Acétone <i>shall apply until 2021-12-31</i>	Short time value	1000 ppm
Acétone <i>shall apply from 2022-01-01</i>	Short time value	492 ppm
	Short time value	1187 mg/m ³
Acétone <i>shall apply until 2021-12-31</i>	Short time value	2420 mg/m ³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m ³
	Short time value	400 ppm
	Short time value	1000 mg/m ³
Carbone (dioxyde de)	Time-weighted average exposure limit 8 h	5000 ppm
	Time-weighted average exposure limit 8 h	9131 mg/m ³
	Short time value	30000 ppm
	Short time value	54784 mg/m ³
Cyclohexane	Time-weighted average exposure limit 8 h	100 ppm
	Time-weighted average exposure limit 8 h	350 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
n-Hexane	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	72 mg/m ³

The Netherlands

Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m ³
	Short time value (Public occupational exposure limit value)	1002 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m ³
Cyclohexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	700 mg/m ³
	Short time value (Public occupational exposure limit value)	400 ppm
	Short time value (Public occupational exposure limit value)	1400 mg/m ³
Kooldioxide	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5000 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	9000 mg/m ³
	Short time value (Public occupational exposure limit value)	40 ppm
n-Hexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	72 mg/m ³
	Short time value (Public occupational exposure limit value)	40 ppm
	Short time value (Public occupational exposure limit value)	144 mg/m ³

France

Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m ³
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m ³
Carbone (dioxyde de)	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	5000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	9000 mg/m ³

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

5 / 25

SOLVETRON AEROSOL

Cyclohexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	700 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	375 ppm
	Short time value (VL: Valeur non réglementaire indicative)	1300 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	72 mg/m ³

Germany

Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m ³
Cyclohexan	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	700 mg/m ³
Kohlenstoffdioxid	Time-weighted average exposure limit 8 h (TRGS 900)	5000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	9100 mg/m ³
n-Hexan	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m ³
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m ³

Austria

2-Propanol Kurzzeitwert für Großguss	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	2000 mg/m ³
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m ³
Aceton	Tagesmittelwert (MAK)	500 ppm
	Tagesmittelwert (MAK)	1200 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	4800 mg/m ³
Cyclohexan	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	700 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2800 mg/m ³
Kohlenstoffdioxid	Tagesmittelwert (MAK)	5000 ppm
	Tagesmittelwert (MAK)	9000 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	10000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	18000 mg/m ³
n-Hexan	Tagesmittelwert (MAK)	20 ppm
	Tagesmittelwert (MAK)	72 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	80 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	288 mg/m ³
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m ³

UK

Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m ³
Carbon dioxide	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	5000 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	9150 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	15000 ppm
	Short time value (Workplace exposure limit (EH40/2005))	27400 mg/m ³

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

6 / 25

SOLVETRON AEROSOL

Cyclohexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	100 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	350 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1050 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	20 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	72 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m ³

USA (TLV-ACGIH)

2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Carbon dioxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5000 ppm
	Short time value (TLV - Adopted Value)	30000 ppm
Cyclohexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	100 ppm
n-Hexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	
Cyclohexan (1,2-Cyclohexandiol (nach Hydrolyse))	Urin: bei langzeitexposition: am schichtende nach mehreren vorangegangenen schichten expositionsende, bzw. schichtende	150 mg/g Kreatinin	
Hexan (n-Hexan) (2,5-Hexandiol plus 4,5-Dihydroxy-2-Hexanon (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende	5 mg/l	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific
Acetone (Acetone)	Urine: end of shift	25 mg/L	Nonspecific
Cyclohexane (1,2-Cyclohexanediol)	: end of shift at end of workweek	50 mg/g creatinine	Nonspecific - Intended changes
n-Hexane (2,5-Hexanedione)	Urine: end of shift	0,5 mg/L	Without hydrolysis

8.1.2 Sampling methods

Product name	Test	Number
Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Acetone	OSHA	69
Cyclohexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
Cyclohexane	OSHA	1022
Cyclohexane	OSHA	7
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	OSHA	109
n-Hexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
n-Hexane (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
n-Hexane (Volatile Organic compounds)	NIOSH	2549
n-Hexane	OSHA	2248
n-Hexane	OSHA	7

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

7 / 25

SOLVETRON AEROSOL

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2085 mg/m ³	
	Long-term systemic effects dermal	300 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5306 mg/m ³	
	Long-term systemic effects dermal	13964 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m ³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1210 mg/m ³	
	Acute local effects inhalation	2420 mg/m ³	
	Long-term systemic effects dermal	186 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	75 mg/m ³	
	Long-term systemic effects dermal	11 mg/kg bw/day	

cyclohexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	700 mg/m ³	
	Acute systemic effects inhalation	1400 mg/m ³	
	Long-term local effects inhalation	700 mg/m ³	
	Acute local effects inhalation	1400 mg/m ³	
	Long-term systemic effects dermal	2016 mg/kg bw/day	

DNEL/DMEL - General population

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	447 mg/m ³	
	Long-term systemic effects dermal	149 mg/kg bw/day	
	Long-term systemic effects oral	149 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1131 mg/m ³	
	Long-term systemic effects dermal	1377 mg/kg bw/day	
	Long-term systemic effects oral	1301 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m ³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	200 mg/m ³	
	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects oral	62 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	16 mg/m ³	
	Long-term systemic effects dermal	5.3 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	

cyclohexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	206 mg/m ³	
	Acute systemic effects inhalation	412 mg/m ³	
	Long-term local effects inhalation	206 mg/m ³	
	Acute local effects inhalation	412 mg/m ³	
	Long-term systemic effects dermal	1186 mg/kg bw/day	
	Long-term systemic effects oral	59.4 mg/kg bw/day	

PNEC

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

8 / 25

SOLVETRON AEROSOL

propan-2-ol

Compartments	Value	Remark
Fresh water	140.9 mg/l	
Fresh water (intermittent releases)	140.9 mg/l	
Marine water	140.9 mg/l	
STP	2251 mg/l	
Fresh water sediment	552 mg/kg sediment dw	
Marine water sediment	552 mg/kg sediment dw	
Soil	28 mg/kg soil dw	
Oral	160 mg/kg food	

acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Fresh water (intermittent releases)	21 mg/l	
STP	100 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	

cyclohexane

Compartments	Value	Remark
Fresh water	44.7 µg/l	
Fresh water (intermittent releases)	9 µg/l	
Marine water	4.47 µg/l	
Marine water (intermittent releases)	0.9 µg/l	
STP	3.24 mg/l	
Fresh water sediment	3.6 mg/kg sediment dw	
Marine water sediment	0.36 mg/kg sediment dw	
Soil	0.694 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
butyl rubber	> 480 minutes	0.7 mm	Class 6	Good resistance

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (aerosol)
Explosion limits	1.1 - 13 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	Not applicable (aerosol)
Boiling point	-57 °C - 95 °C
Relative vapour density	No data available in the literature

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

9 / 25

SOLVETRON AEROSOL

Vapour pressure	8530 hPa ; 20 °C ; Liquid
Solubility	Water ; insoluble
Relative density	0.72 ; 20 °C
Absolute density	719 kg/m ³ ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (non-soluble in water)

9.2. Other information

Evaporation rate	7 ; Butyl acetate
------------------	-------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Unstable on exposure to heat.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

SOLVETRON AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 5840 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50		> 2800 mg/kg bw	24 h	Rat (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 23.3 mg/l air	4 h	Rat (male / female)	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.354 mg/l	4 h	Rat (male)	Read-across	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

10 / 25

SOLVETRON AEROSOL

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50		> 15800 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50		76 mg/l	4 h	Rat (female)	Weight of evidence	
					(male)		

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	16000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 17.6 mg/l air	24 h	Rat (male)	Experimental value	

cyclohexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw		Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 19.07 mg/l	4 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

SOLVETRON AEROSOL

No (test) data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating			7 days	Rabbit	Read-across	Single treatment
Skin	Irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405	72 h	72 hours	Rabbit	Read-across	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Not irritating		3 day(s)	24; 48; 72 hrs; 4 days	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature study	

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

11 / 25

SOLVETRON AEROSOL

n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		72 hours	Rabbit	Read-across	
Skin	Irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Read-across	

cyclohexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Slightly irritating	Equivalent to OECD 405		1 hour	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating; category 2					Annex VI	

Conclusion

Causes skin irritation.
Causes serious eye irritation.
Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

SOLVETRON AEROSOL

No (test) data on the mixture available
Judgement is based on the relevant ingredients
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male / female)	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (male / female)	Read-across	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Experimental value	

n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse	Read-across	

cyclohexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	EU Method B.6			Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for inhalation
Not classified as sensitizing for skin

Specific target organ toxicity

SOLVETRON AEROSOL

No (test) data on the mixture available
Classification is based on the relevant ingredients

SOLVETRON AEROSOL

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	12350 mg/m ³ air		No adverse systemic effects	26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (vapours)	LOAEL	Equivalent to OECD 413	1650 mg/m ³ air	Central nervous system	CNS depression	26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10504 mg/m ³ air		No effect	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 413	31652 mg/m ³ air	Liver; kidney	Organ damage	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm		No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male / female)	Experimental value

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	4.86 mg/kg bw/day - 5.95 mg/kg bw/day		No effect	13 week(s)	Mouse (male / female)	Experimental value
Oral (drinking water)	LOAEL	Equivalent to OECD 408	11.3 mg/kg bw/day	Liver	Histopathology		Mouse (female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Subchronic toxicity test	19000 ppm		No effect	8 weeks (5 days / week)	Rat (male)	Experimental value
Inhalation (vapours)	Dose level	Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Epidemiological study

n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	567 mg/kg bw/day - 1135 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rat (male)	Experimental value
Oral (stomach tube)	LOAEL	Subchronic toxicity test	3956 mg/kg bw/day	Central nervous system	neurotoxic effects	17 weeks (5 days / week)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Subchronic toxicity test	3000 ppm	Central nervous system	neurotoxic effects	16 weeks (daily)	Rat (male)	Experimental value
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Annex VI

cyclohexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	EPA OPPTS 870.3465	7000 ppm		No adverse systemic effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	NOAEC	EPA OPPTS 870.3465	500 ppm	Central nervous system	No effect	6 h	Rat (male / female)	Experimental value

Conclusion

May cause drowsiness or dizziness.
Not classified for subchronic toxicity

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

13 / 25

SOLVETRON AEROSOL

Mutagenicity (in vitro)

SOLVETRON AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 476	Human lymphocytes	No effect	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

acetone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

cyclohexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

Mutagenicity (in vivo)

SOLVETRON AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (drinking water))	Micronucleus test	13 week(s)	Mouse (male / female)		Literature study

n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))		8 weeks (6h / day, 5 days / week)	Mouse (male)		Experimental value

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

14 / 25

SOLVETRON AEROSOL

cyclohexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

SOLVETRON AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9016 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Carcinogenic toxicity study	79 mg	51 weeks (3 times / week)	Mouse (female)	No carcinogenic effect		Literature study

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	3000 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	No carcinogenic effect		Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	Tumor formation	Liver	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (male)	No carcinogenic effect		Read-across

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

SOLVETRON AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	31680 mg/m ³ air	10 days (6h / day)	Mouse	No effect		Read-across
Maternal toxicity	NOAEL	Equivalent to OECD 414	10560 mg/m ³ air	10 days (6h / day)	Rat (female)	No effect		Read-across
	LOAEL	Equivalent to OECD 414	31680 mg/m ³ air	10 days (6h / day)	Rat (female)	Lung tissue affection/degeneration	Lungs	Read-across
Effects on fertility	NOAEL (P/F1)	Equivalent to OECD 416	31680 mg/m ³ air		Rat (male / female)	No effect		Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	> 7000 ppm	10 days (6h / day)	Rat	No effect		Read-across
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h / day)	Rat (female)	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm		Rat (male / female)	No effect		Read-across

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

15 / 25

SOLVETRON AEROSOL

propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
	LOAEC	Equivalent to OECD 414	11000 mg/kg bw/day	14 days (gestation, daily)	Rat	Fetotoxicity	Foetus	Experimental value
Maternal toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	11000 ppm	14 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL		900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Experimental value
	LOAEL		3400 mg/kg bw/day	13 week(s)	Rat (male)	Adverse effects on fertility	Male reproductive organ	Experimental value

n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	3000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm	≥ 13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

cyclohexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	7000 ppm	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	500 ppm - 2000 ppm	10 days (6h / day)	Rat	No effect		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	500 ppm - 2000 ppm	> 11 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

SOLVETRON AEROSOL

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation	NOAEC	Equivalent to OECD 424	9000 ppm	Central nervous system	Overall effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Skin				Skin	Skin dryness or cracking			Literature study

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

16 / 25

SOLVETRON AEROSOL

cyclohexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
	NOAEC		2000 ppm		neurotoxic effects	6 h	Rat (male)	Experimental value

Chronic effects from short and long-term exposure

SOLVETRON AEROSOL

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

SOLVETRON AEROSOL

No (test) data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 13.4 mg/l WAF	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	3.0 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	13 mg/l WAF	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; GLP
Long-term toxicity fish	NOELR		1.534 mg/l	28	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Toxicity aquatic micro-organisms	EL50		26.81 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth rate

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		18.27 mg/l	96 h	Oncorhynchus mykiss		Fresh water	QSAR
Acute toxicity crustacea	EL50		31.9 mg/l	48 h	Daphnia magna		Fresh water	QSAR
Toxicity algae and other aquatic plants	EL50		13.56 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	QSAR
Long-term toxicity fish	NOELR		4.089 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		7.138 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

Classification of this substance is debatable as it does not correspond to the conclusion from the test

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC		2344 µmol/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

17 / 25

SOLVETRON AEROSOL

acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	6210 mg/l - 8120 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	LC50		8800 mg/l	48 h	Daphnia pulex	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEC		530 mg/l		Algae		Fresh water	
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2212 mg/l	28 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value
Toxicity aquatic micro-organisms	EC50	Equivalent to OECD 209	61.15 g/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value

n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		12.51 mg/l	96 h	Oncorhynchus mykiss		Fresh water	Estimated value; Lethal
Acute toxicity crustacea	EL50		21.85 mg/l	48 h	Daphnia magna		Fresh water	Estimated value; Locomotor effect
Toxicity algae and other aquatic plants	EL50		9.285 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	Estimated value; Growth rate
	NOELR		2.077 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	Estimated value; Growth rate
Long-term toxicity fish	NOELR		2.8 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	Estimated value; Growth rate
Long-term toxicity aquatic crustacea	NOELR		4.888 mg/l	21 day(s)	Daphnia magna		Fresh water	Estimated value; Reproduction
Toxicity aquatic micro-organisms	EL50		48.39 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth

cyclohexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	4.53 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	EC50	Equivalent to OECD 202	0.9 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EC50	Equivalent to OECD 201	9.317 mg/l	72 h	Pseudokirchneriella subcapitata			Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro-organisms	IC50		29 mg/l	15 h	Aerobic micro-organisms			Experimental value; Oxygen consumption

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Experimental value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Read-across

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	17.668 h	1.5E6 /cm ³	Calculated value

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

18 / 25

SOLVETRON AEROSOL

acetone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90.9 %	28 day(s)	Experimental value

n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; Oxygen consumption	28 day(s)	Read-across

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	23.515 h	1.5E6 /cm ³	Calculated value

cyclohexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	77 %; Oxygen consumption	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	15.14 h	1.5E6 /cm ³	QSAR

Conclusion

Water

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

SOLVETRON AEROSOL

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Log Kow

Method	Remark	Value	Temperature	Value determination
		> 3		

hydrocarbons, C6, isoalkanes, < 5% n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		501.187		Pimephales promelas	Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		3.34	20 °C	Read-across

propan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

acetone

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.23		Test data

n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		501.187		Pimephales promelas	Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		4	20 °C	Experimental value

cyclohexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		167 l/kg; Fresh weight		Pimephales promelas	QSAR

Log Kow

Method	Remark	Value	Temperature	Value determination
		3.44	25 °C	Experimental value

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

SOLVETRON AEROSOL

hydrocarbons, C6, isoalkanes, < 5% n-hexane

(log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	93.6 %	0 %	2.1 %	0.5 %	3.8 %	Calculated value

propan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.185 - 0.541	Calculated value

acetone

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.374 - 0.988	Calculated value

n-hexane

(log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	QSAR

cyclohexane

(log) Koc

Parameter	Method	Value	Value determination
log Koc		2.89	Calculated value

Conclusion

Contains component(s) that adsorb(s) into the soil
 Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

SOLVETRON AEROSOL

Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)
 None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

propan-2-ol

Groundwater

Groundwater pollutant

acetone

Groundwater

Groundwater pollutant

cyclohexane

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
 Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

14 06 03* (waste organic solvents, refrigerants and foam/aerosol propellants: other solvents and solvent mixtures). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.
 Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

20 / 25

SOLVETRON AEROSOL

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Hazard identification number	
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	yes
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Hazard identification number	23
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	yes
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	yes
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

21 / 25

SOLVETRON AEROSOL

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

Explosives precursors

Due to the presence of one or more components in this mixture, acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

VOC content Directive 2010/75/EU

VOC content	Remark
97.000 %	
691.480 g/l	

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· hydrocarbons, C7, n-alkanes, isoalkanes, cyclics · hydrocarbons, C6, isoalkanes, < 5% n-hexane · propan-2-ol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

22 / 25

SOLVETRON AEROSOL

<ul style="list-style-type: none"> · acetone · n-hexane · cyclohexane 	<p>types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>with ornamental aspects,</p> <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none"> — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <ul style="list-style-type: none"> a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage”; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
<ul style="list-style-type: none"> · hydrocarbons, C7, n-alkanes, isoalkanes, cyclics · hydrocarbons, C6, isoalkanes, < 5% n-hexane · propan-2-ol · acetone · n-hexane · cyclohexane 	<p>Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopee” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>“For professional users only”.</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
<ul style="list-style-type: none"> · cyclohexane 	<p>Cyclohexane</p>	<p>1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g.</p> <p>2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.</p> <p>3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows:</p> <ul style="list-style-type: none"> — This product is not to be used under conditions of poor ventilation. — This product is not to be used for carpet laying.”
<ul style="list-style-type: none"> · propan-2-ol · acetone · n-hexane · cyclohexane 	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p>	<p>Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081</p>

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

23 / 25

SOLVETRON AEROSOL

The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

National legislation Belgium SOLVETRON AEROSOL

No data available

National legislation The Netherlands SOLVETRON AEROSOL

Waterbezwaarlijkheid	A (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

n-hexane

SZW - Lijst van voor de voortplanting giftige stoffen (vruchtbaarheid)	n-hexaan; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (vruchtbaarheid); 2
--	--

National legislation France SOLVETRON AEROSOL

No data available

n-hexane

Catégorie toxique pour la reproduction	n-Hexane; R2
--	--------------

National legislation Germany SOLVETRON AEROSOL

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
-----------------------	-------------------------------------

WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

TA-Luft	5.2.5/I
---------	---------

hydrocarbons, C6, isoalkanes, < 5% n-hexane

TA-Luft	5.2.5/I
---------	---------

propan-2-ol

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

acetone

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	---

n-hexane

TA-Luft	5.2.5/I
---------	---------

TRGS900 - Risiko der Fruchtschädigung	n-Hexan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

cyclohexane

TA-Luft	5.2.5/I
---------	---------

National legislation Austria SOLVETRON AEROSOL

No data available

n-hexane

Fortpflanzungsgefährdend [Beeinträchtigung der Fortpflanzungsfähigkeit (Fruchtbarkeit)]	n-Hexan; f
---	------------

National legislation United Kingdom SOLVETRON AEROSOL

No data available

Other relevant data

SOLVETRON AEROSOL

No data available

propan-2-ol

IARC - classification	3; Isopropanol
-----------------------	----------------

TLV - Carcinogen	2-propanol; A4
------------------	----------------

acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

n-hexane

TLV - Skin absorption	n-Hexane; Skin; Danger of cutaneous absorption
-----------------------	--

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 3.2, 8, 9, 15

Publication date: 2001-02-13

Date of revision: 2021-10-20

Revision number: 0900

BIG number: 33450

24 / 25

SOLVETRON AEROSOL

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs (nervous system) through prolonged or repeated exposure if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
Erc50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.