

Easy Weld Primer



METAL PROTECTION BEFORE AND AFTER WELDING

- ✓ Ideal for welding without splashing.
- ✓ Optimal protection.
- ✓ Unique adhesion to steel and galvanized steel.

Technical Info

- Composition: synthetic polyvinyl resins, iron oxides, silicates, aliphatic and aromatic hydrocarbons.
- Colour: red-brown.
- Aspect: matt.
- Viscosity: 17 sec. DIN4 (20°C).
- Dry substances: 72% (weight).
- Drying time:
 - dust dry: 10 min. 20°C / 65% R.H.;
 - touch dry 30 min. 20°C / 65% R.H.;
 - dry: 1 hour 20°C / 65% R.H.
- Recommended layer thickness: 9-16 micron.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Easy Weld Primer - aerosol 500ml

119010000

Product [EPR]

Characteristics

Steel protection against rust. Easy to weld without splashing or burning away, with spot welding or semi-automatic. Forms a perfect rust protection with optimum adhesion. Perfectly sprayable thanks to its fine composition, with a spray pattern like that of a conventional spray gun.

Use

- After releasing the mixing ball, shake the can well before use.
- Apply on a clean and dry surface. If necessary, clean with Safety Clean and / or Multifoam.
- Apply only 1 thin covering layer. Spraying distance: 30 cm.
- Spray the cup empty after use with the inverted canister.
- Respect drying times.

Easy Weld Primer is not a primer before paintwork. Apply a Novafill Flex primer before finishing with lacquer.