



Nova Finish Primer

Surface Protection & Treatment

FINE PRIMER

- ✓ Primer and elastifier with anti-corrosive elements.
- ✓ Perfect adhesion on most hard materials, even on PVC.
- ✓ Can be sanded quickly and easily.
- ✓ With width control and flow control in the spray head.

Technical Info

- Base: acrylic.
- Odour: characteristic.
- Vapour pressure at 20 °C: 8300 hPa.
- Density at 20 °C: 0,89 g/cm³.
- Solubility in water: none.
- Mixability in water: small mixable.
- VOC (EU): 791,7 g/l.
- Filling capacity: +/- 40 micron.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Nova Finish Primer black - aerosol 500ml	120822000
Nova Finish Primer dark grey - aerosol 500ml	120812000
Nova Finish Primer white - aerosol 500ml	120832000

Product [FPR]

Characteristics

Nova Finish Primer is a fine primer specially developed to lacquer it with the newest water-based lacquers afterwards. Nova Finish Primer combines elastisator and adhesive capacities with rust-proof elements. Thans to Nova Finish Primer you don't have to throw away paints residues anymore and clean guns for small repairs. Nova Finish Primer is easy to use. To guarantee the covering capacity of the lacquer you use, Nova Finish Primer is available in 3 colours. Nova finish Primer has a fine covering that makes the finishin easier and needs less sanding. Nova Finish Primer is capable for drying fast with infrared.

Use

Thanks to the adjustable nozzle this aerosol can also be used as a spraying gun: the nozzle is adjustable in width and flow. It is suitable for accelerated with infrared.

- Shake well before using
- Degrease surface with Safety Clean and/or Multifoam, then sand until matte.
- Always apply Nova Finish Primer in several thin layers. Spray distance: +/- 25 cm
- Empty the nozzle spraying with the can upside down.

After drying (+/- 20 min) Nova Finish Primer can be sanded (wet and dry). Can be painted with most common paints. With synthetic materials that contain PE or PP, Nova Finish Primer can have less or even bad adhesion. On these synthetic surfaces we recommend, after sanding, to use first Seal & Bond Special Primer before using Nova Finish Primer.

Which Novafill Flex to use?

- On metal as first layer: Nova Finish Primer, because of its rust-proof capacity.
- On other surfaces (as well as synthetic materials) as first layer: Novafill Flex or Novafill Flex 2, because of their adhesive capacities (apply first Seal & Bond Special Primer on difficult synthetic materials).
- Following layers according to the filling needed: Novafiller, Novafill Flex or Novafill Flex 2.
- As a final layer, before painting, Nova Finish Primer is recommended by his fine structure: the finish is easy, saves time by less sanding