

PUP-001 PUC Primer



1K ADHESION PRIMER AND ANTI-CORROSION

- ✓ For PUC-001 2K PU Coating.
- ✓ On metal and wood.
- ✓ 1K epoxy.
- ✓ Brief drying time.

Technical Info

- Base: 1K epoxy.
- Colour: grey.
- Odour: characteristic.
- Self-ignition temperature (DIN 51794): +235°C.
- Vapour pressure at 20°C: 5,200 hPa.
- Density at 20°C (DIN 53217): 0.873 g/cm³.
- VOC: 77.93 %.
- Shelf life: 24 months, store in a cold and dry place.
- Safety measures: please refer to the safety data sheet.

Packing

PUP-001 PUC Primer - aerosol 400ml

140110000

Product [PUP-001]

Characteristics

PUP-001 PUC Primer ensures excellent adhesion of PUC-001 2K PU Coating on difficult, smooth surfaces, such as metal, wood and old paint layers. Moreover, it provides years of protection against oxidation.

Use

- Apply to a clean, dry and stable substrate. If necessary, first clean with Safety Clean and/or Multifoam.
- Shake well for two minutes and apply to a test piece.
- Apply a thin, uniform layer of 20 to 30 cm.
- Allow gas to evaporate briefly and apply a second thin layer.
- Empty the nozzle spraying with the can upside down.