



# XPR-90 Safe Remover

FOR REMOVAL OF HARDENED GREASE AND SILICONES, GLUE AND WAX

- ✓ Does not run or drip.
- ✓ Long working time.
- ✓ With powerful lime extracts.

## Technical Info

- Composition: aliphatic hydrocarbon solvent, binder, and citrus extracts.
- Boiling point/boiling range °C: 130 - 166.
- Vapour pressure/20°C hPa: 4.6.
- Relative density/20°C: 0.75.
- Physical state/20°C: liquid.
- Flashpoint °C: 24.
- Self-combustion °C: 200.
- Water solubility: insoluble.
- Odour: distinctive.
- Dynamic viscosity mPa.s/20°C: 1.
- Kinematic viscosity, mm<sup>2</sup>/s/20°C: 1.
- Volatile organic compound (VOC) %: 100.
- Volatile organic compound (VOC) g/l: 710.
- For specific technical information per package, please consult the SDS and MSDS.

## Packing

XPR-90 Safe Remover - aerosol 500ml

683840000

## Product [SAR90]

### Characteristics

Versatile cleaner in gel form, also suitable for vertical applications. An aliphatic hydrocarbon solvent with added lime extracts.

### Applications

Safe to use on most materials to remove wax, glue, grease and silicone residues, even hardened ones.

## Use

- Apply and allow to act according to pollution.
- Rub off the loosened soiling.
- If necessary, repeat the treatment.
- Always rinse the cleaned surface with clean water.