

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## WOODFILLER

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : WOODFILLER  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Paint

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements



Contains: acetone; n-butyl acetate.

**Signal word** Danger

##### H-statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

##### P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 3.2; 9; 12; 15

Revision number: 0300

Publication date: 2011-07-08

Date of revision: 2020-11-25

Product number: 51293

1 / 26

# WOODFILLER

P251 Do not pierce or burn, even after use.  
 P280 Wear eye protection.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

## Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
acetone 01-2119471330-49	67-64-1 200-662-2	20%<C<25%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
n-butyl acetate 01-2119485493-29	123-86-4 204-658-1	12.5% <C<20%	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
2-methoxy-1-methylethyl acetate 01-2119475791-29	108-65-6 203-603-9	2.5%<C<5%	Flam. Liq. 3; H226	(1)(2)(10)	Constituent	
butan-1-ol 01-2119484630-38	71-36-3 200-751-6	C<2.5%	Flam. Liq. 3; H226 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335 STOT SE 3; H336	(1)(2)(10)	Constituent	
trizinc bis(orthophosphate) 01-2119485044-40	7779-90-0 231-944-3	C<1%	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)	Constituent	M: 1 (Acute, ECHA (registration dossier)) M: 1 (Chronic, ECHA (registration dossier))
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C<2.5%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5	5%<C<10%	Carc. 2; H351	(1)(2)	Constituent	
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	12.5% <C<20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	5%<C<10%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant	
butane	106-97-8 203-448-7	2.5%<C<5%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)(21)	Propellant	
isobutane 01-2119485395-27	75-28-5 200-857-2	2.5%<C<5%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas;	(1)(2)(10)(21)	Propellant	

- (1) For H- and EUH-statements in full: see heading 16  
 (2) Substance with a Community workplace exposure limit  
 (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006  
 (21) 1,3-butadiene <0.1%

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

2 / 26

# WOODFILLER

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

## 4.2. Most important symptoms and effects, both acute and delayed

### 4.2.1 Acute symptoms

#### After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Dizziness. Drowsiness.

#### After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

#### After eye contact:

Irritation of the eye tissue.

#### After ingestion:

No effects known.

### 4.2.2 Delayed symptoms

No effects known.

## 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion CO and CO2 are formed and formation of metal oxides.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

#### Suitable protective clothing

See heading 8.2

### 6.2. Environmental precautions

Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Do not wash down with water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

# WOODFILLER

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Remove contaminated clothing immediately.

## 7.2. Conditions for safe storage, including any incompatibilities

### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Store in a dry area. Keep container in a well-ventilated place. Fireproof storeroom. Meet the legal requirements.

### 7.2.2 Keep away from:

Heat sources, ignition sources.

### 7.2.3 Suitable packaging material:

Aerosol.

### 7.2.4 Non suitable packaging material:

No data available

## 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### EU

2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	275 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	550 mg/m <sup>3</sup>
Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m <sup>3</sup>
n-Butyl acetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	241 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	150 ppm
	Short time value (Indicative occupational exposure limit value)	723 mg/m <sup>3</sup>

#### Belgium

# WOODFILLER

Acétate de 2-(1-méthoxy)propyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	275 mg/m <sup>3</sup>
	Short time value	100 ppm
	Short time value	550 mg/m <sup>3</sup>
Acétate de n-butyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	238 mg/m <sup>3</sup>
	Short time value	150 ppm
	Short time value	712 mg/m <sup>3</sup>
Acétone	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1210 mg/m <sup>3</sup>
	Short time value	1000 ppm
	Short time value	2420 mg/m <sup>3</sup>
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m <sup>3</sup>
	Short time value	400 ppm
	Short time value	1000 mg/m <sup>3</sup>
Alcool n-butylique	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	62 mg/m <sup>3</sup>
Butane, tous isomères: iso-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m <sup>3</sup>
Titane (dioxyde de)	Time-weighted average exposure limit 8 h	10 mg/m <sup>3</sup>

## The Netherlands

1-Methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
1-methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	550 mg/m <sup>3</sup>
Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	501 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	1002 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m <sup>3</sup>

## France

Acétate de 2-méthoxy-1-méthyléthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	275 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	550 mg/m <sup>3</sup>
Acétate de n-butyle	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	150 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	710 mg/m <sup>3</sup>
	Short time value (VL: Valeur non réglementaire indicative)	200 ppm
	Short time value (VL: Valeur non réglementaire indicative)	940 mg/m <sup>3</sup>
Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m <sup>3</sup>
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m <sup>3</sup>
Alcool n-butylique	Short time value (VL: Valeur non réglementaire indicative)	50 ppm
	Short time value (VL: Valeur non réglementaire indicative)	150 mg/m <sup>3</sup>

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

5 / 26

# WOODFILLER

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m <sup>3</sup>
Titane (dioxyde de), en Ti	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m <sup>3</sup>

## Germany

2-Methoxy-1-méthylethylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	270 mg/m <sup>3</sup>
Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m <sup>3</sup>
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Butan-1-ol	Time-weighted average exposure limit 8 h (TRGS 900)	100 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	310 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m <sup>3</sup>
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
n-Butylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	62 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	300 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m <sup>3</sup>

## UK

1-Methoxypropyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	274 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	548 mg/m <sup>3</sup>
Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m <sup>3</sup>
Butan-1-ol	Short time value (Workplace exposure limit (EH40/2005))	50 ppm
	Short time value (Workplace exposure limit (EH40/2005))	154 mg/m <sup>3</sup>
Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>
Butyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	150 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	724 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	966 mg/m <sup>3</sup>
Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m <sup>3</sup>
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m <sup>3</sup>

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

6 / 26

# WOODFILLER

Titanium dioxide respirable	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	4 mg/m <sup>3</sup>
Titanium dioxide total inhalable	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	10 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
Butyl acetates, all isomers	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
	Short time value (TLV - Adopted Value)	150 ppm
n-Butanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
Titanium dioxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	10 mg/m <sup>3</sup>

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### Germany

Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	
Butan-1-ol (1-Butanol) (Butan-1-ol (1-Butanol) (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende	10 mg/g Kreatinin	
Butan-1-ol (1-Butanol) (Butan-1-ol (1-Butanol) (nach Hydrolyse))	Urin: vor nachfolgender schicht	2 mg/g Kreatinin	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	
Vitamin K-Antagonisten (Quick-Wert)	Vollblut: keine beschränkung	Reduktion auf nicht weniger als 70%	Ableitung des BGW als Höchstwert wegen akut toxischer Effekte

## USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific
Acetone (Acetone)	Urine: end of shift	25 mg/L	Nonspecific

## 8.1.2 Sampling methods

Product name	Test	Number
1-Methoxy-2-Propyl Acetate	OSHA	99
Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Acetone	OSHA	69
Butanol (Volatile Organic compounds)	NIOSH	2549
Butyl acetate (Volatile Organic compounds)	NIOSH	2549
Butyl Alcohol	OSHA	7
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	OSHA	109
n-Butyl Acetate (Esters I)	NIOSH	1450
n-Butyl Acetate	OSHA	1009
n-Butyl Alcohol (Alcohols Combined)	NIOSH	1405
n-Butyl Alcohol (Alcohols II)	NIOSH	1401
Propylene glycol monomethyl ether acetate (glycol ethers)	NIOSH	2554
TiO <sub>2</sub>	NIOSH	7302
TiO <sub>2</sub>	NIOSH	7304
Zinc & Cpds (as Zn)	NIOSH	7030

## 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

## 8.1.4 Threshold values

### DNEL/DMEL - Workers

#### acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1210 mg/m <sup>3</sup>	
	Acute local effects inhalation	2420 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	186 mg/kg bw/day	

# WOODFILLER

## n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	300 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	600 mg/m <sup>3</sup>	
	Long-term local effects inhalation	300 mg/m <sup>3</sup>	
	Acute local effects inhalation	600 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	11 mg/kg bw/day	
	Acute systemic effects dermal	11 mg/kg bw/day	

## 2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	275 mg/m <sup>3</sup>	
	Acute local effects inhalation	550 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	796 mg/kg bw	

## butan-1-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	310 mg/m <sup>3</sup>	

## trizinc bis(orthophosphate)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	83 mg/kg bw/day	

## propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	888 mg/kg bw/day	

## **DNEL/DMEL - General population acetone**

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	200 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects oral	62 mg/kg bw/day	

## n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	35.7 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	300 mg/m <sup>3</sup>	
	Long-term local effects inhalation	35.7 mg/m <sup>3</sup>	
	Acute local effects inhalation	300 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	6 mg/kg bw/day	
	Acute systemic effects dermal	6 mg/kg bw/day	
	Long-term systemic effects oral	2 mg/kg bw/day	
	Acute systemic effects oral	2 mg/kg bw/day	

## 2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	33 mg/m <sup>3</sup>	
	Long-term local effects inhalation	33 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	320 mg/kg bw	
	Long-term systemic effects oral	36 mg/kg bw	

## butan-1-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	55.357 mg/m <sup>3</sup>	
	Long-term local effects inhalation	155 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	3.125 mg/kg bw/day	
	Long-term systemic effects oral	1.562 mg/kg bw/day	

## trizinc bis(orthophosphate)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.5 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	83 mg/kg bw/day	
	Long-term systemic effects oral	0.83 mg/kg bw/day	

## propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

## **PNEC**



# WOODFILLER

## acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Fresh water (intermittent releases)	21 mg/l	
STP	100 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	

## n-butyl acetate

Compartments	Value	Remark
Fresh water	0.18 mg/l	
Marine water	0.018 mg/l	
Fresh water (intermittent releases)	0.36 mg/l	
STP	35.6 mg/l	
Fresh water sediment	0.981 mg/kg sediment dw	
Marine water sediment	0.098 mg/kg sediment dw	
Soil	0.09 mg/kg soil dw	

## 2-methoxy-1-methylethyl acetate

Compartments	Value	Remark
Fresh water	0.635 mg/l	
Marine water	0.064 mg/l	
Fresh water (intermittent releases)	6.35 mg/l	
STP	100 mg/l	
Fresh water sediment	3.29 mg/kg sediment dw	
Marine water sediment	0.329 mg/kg sediment dw	
Soil	0.29 mg/kg soil dw	

## butan-1-ol

Compartments	Value	Remark
Fresh water	0.082 mg/l	
Marine water	0.008 mg/l	
Fresh water (intermittent releases)	2.25 mg/l	
STP	2476 mg/l	
Fresh water sediment	0.324 mg/kg sediment dw	
Marine water sediment	0.032 mg/kg sediment dw	
Soil	0.017 mg/kg soil dw	

## trizinc bis(orthophosphate)

Compartments	Value	Remark
Fresh water	20.6 µg/l	
Marine water	6.1 µg/l	
STP	100 µg/l	
Fresh water sediment	117.8 mg/kg sediment dw	
Marine water sediment	56.5 mg/kg sediment dw	
Soil	35.6 mg/kg soil dw	

## propan-2-ol

Compartments	Value	Remark
Fresh water	140.9 mg/l	
Fresh water (intermittent releases)	140.9 mg/l	
Marine water	140.9 mg/l	
STP	2251 mg/l	
Fresh water sediment	552 mg/kg sediment dw	
Marine water sediment	552 mg/kg sediment dw	
Soil	28 mg/kg soil dw	
Oral	160 mg/kg food	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

# WOODFILLER

Materials	Measured breakthrough time	Thickness	Protection index	Remark
butyl rubber	> 480 minutes	0.4 mm	Class 6	

**c) Eye protection:**

Protective goggles (EN 166).

**d) Skin protection:**

Protective clothing (EN 14605 or EN 13034).

**8.2.3 Environmental exposure controls:**

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Solvent-like odour
Odour threshold	No data available in the literature
Colour	Beige
Particle size	Not applicable (aerosol)
Explosion limits	1.2 - 26.2 vol % ; Liquid
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	Not applicable (aerosol)
Boiling point	Not applicable (aerosol)
Relative vapour density	No data available in the literature
Vapour pressure	4000 hPa ; 20 °C ; Liquid
Solubility	Water ; insoluble ; Liquid
Relative density	0.80 ; 20 °C
Absolute density	800 kg/m <sup>3</sup> ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (aerosol)

### 9.2. Other information

Evaporation rate	No data available in the literature
Explosive properties	Not classified
Oxidising properties	Not classified

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

**Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion CO and CO<sub>2</sub> are formed and formation of metal oxides.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

**Acute toxicity**

WOODFILLER

No (test)data on the mixture available

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

10 / 26

# WOODFILLER

Judgement is based on the relevant ingredients

## acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50		> 15800 mg/kg bw	24 h	Rabbit (male)	Weight of evidence	
Inhalation (vapours)	LC50		76 mg/l	4 h	Rat (female)	Weight of evidence	
					(male)		

## n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	10760 mg/kg bw - 12789 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 14112 mg/kg bw		Rabbit (male / female)	Experimental value	
Inhalation (aerosol)	LC50	OECD 403	0.74 mg/l	4 h	Rat (male / female)	Experimental value	

## 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	6190 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation	LC0	Equivalent to OECD 403	10.8 mg/l	3 h	Rat (male)	Experimental value	

## butan-1-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2292 mg/kg bw		Rat (female)	Experimental value	
Oral			category 4			Annex VI	
Dermal	LD50	Equivalent to OECD 402	3430 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 17.76 mg/l air	4 h	Rat (male / female)	Experimental value	

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

## trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC50	Equivalent to OECD 403	> 5.70 mg/l air	4 h	Rat (male / female)	Read-across	

## propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	12882 mg/kg bw	24 h	Rabbit	Experimental value	Converted value
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC50	OECD 403	> 5.09 mg/l	4 h	Rat (male)	Experimental value	

### **Conclusion**

Not classified for acute toxicity

### **Corrosion/irritation**

#### WOODFILLER

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

11 / 26

# WOODFILLER

No (test)data on the mixture available

Classification is based on the relevant ingredients

## acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Not irritating		3 day(s)	24; 48; 72 hrs; 4 days	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature	

## n-butyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Dermal	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## 2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## butan-1-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating	Draize Skin Test		24; 48; 72 hours	Rabbit	Experimental value	
Inhalation	Irritating	Human observation			Human	Experimental value	

## trizinc bis(orthophosphate)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	72 h	1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Patch test	5 day(s)		Rabbit	Read-across	

## propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to OECD 404	4 h	48 hours	Rabbit	Experimental value	

## **Conclusion**

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

## **Respiratory or skin sensitisation**

### WOODFILLER

No (test)data on the mixture available

Judgement is based on the relevant ingredients

## acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Experimental value	

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

12 / 26

# WOODFILLER

## n-butyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig	Experimental value	

## 2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Experimental value	

## butan-1-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (female)	Experimental value	

## trizinc bis(orthophosphate)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Read-across	

## propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (female)	Experimental value	
Inhalation (dust)	Not sensitizing				Mouse (female)	Experimental value	

### **Conclusion**

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

### **Specific target organ toxicity**

#### WOODFILLER

No (test) data on the mixture available

Classification is based on the relevant ingredients

#### acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	4.86 mg/kg bw/day - 5.95 mg/kg bw/day		No effect	13 week(s)	Mouse (male / female)	Experimental value
Oral (drinking water)	LOAEL	Equivalent to OECD 408	11.3 mg/kg bw/day	Liver	Histopathology		Mouse (female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Subchronic toxicity test	19000 ppm		No effect	8 week(s)	Rat (male)	Experimental value
Inhalation (vapours)	Dose level	Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Epidemiological study

#### n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	125 mg/kg bw/day		No effect	13 week(s)	Rat (male / female)	Read-across
Oral (stomach tube)	LOAEL	Subchronic toxicity test	500 mg/kg bw/day	Central nervous system	Central nervous system depression	13 day(s)	Rat (male / female)	Read-across
Inhalation (vapours)	NOAEC	EPA OTS 798.2450	500 ppm		No adverse systemic effects	13 weeks (daily, 5 days / week)	Rat (male / female)	Experimental value

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

13 / 26

# WOODFILLER

## 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 422	≥ 1000 mg/kg		No effect	41 day(s) - 45 day(s)	Rat (male / female)	Experimental value
Oral (stomach tube)	Dose level	US EPA	500 mg/kg bw/day		Drowsiness, dizziness		Rat (male / female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	1838 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rabbit (male)	Read-across
Inhalation (vapours)	NOEL	OECD 453	300 ppm		No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

## butan-1-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	125 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male / female)	Experimental value
Oral (stomach tube)	LOAEL	Subchronic toxicity test	500 mg/kg bw/day	Central nervous system	Central nervous system depression	13 weeks (daily)	Rat (male / female)	Experimental value
Skin	Dose level	Subacute toxicity test	100 %	Skin	Irritation	3 week(s)	Rabbit	Experimental value
Inhalation (vapours)	NOAEL	EPA OTS 798.2450	500 ppm		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	EPA OTS 798.2450	1500 ppm	Central nervous system	Drowsiness, dizziness	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

## trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	OECD 408	31.52 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation	Dose level	Subacute toxicity test	4.6 mg/m <sup>3</sup> air	Lungs	Impairment/d egeneration	6 days (3h / day)	Guinea pig (male)	Read-across

## propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm		No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male / female)	Experimental value

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 408	> 1000 mg/kg bw/day		No effect	90 day(s)	Rat (male / female)	Experimental value
Dermal								Data waiving

### Conclusion

May cause drowsiness or dizziness.  
Not classified for subchronic toxicity

### Mutagenicity (in vitro)

#### WOODFILLER

No (test) data on the mixture available  
Judgement is based on the relevant ingredients  
acetone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

#### n-butyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

14 / 26

# WOODFILLER

## 2-methoxy-1-methylethyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

## butan-1-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 476	Chinese hamster lung fibroblasts (V79)	No effect	Experimental value	

## trizinc bis(orthophosphate)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	EU Method B.13/14	Bacteria (S.typhimurium)		Read-across	

## propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster ovary (CHO)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)		Experimental value	

## Mutagenicity (in vivo)

### WOODFILLER

No (test)data on the mixture available

Judgement is based on the relevant ingredients

### acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (drinking water))	Micronucleus test	13 week(s)	Mouse (male / female)		Literature

### n-butyl acetate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)		Read-across

### butan-1-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)		Experimental value

### trizinc bis(orthophosphate)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Micronucleus test	2 dose(s)/24-hour interval	Mouse (male / female)		Read-across

### propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)		Experimental value

### Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### WOODFILLER

No (test)data on the mixture available

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

15 / 26

# WOODFILLER

Judgement is based on the relevant ingredients

## acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Carcinogenic toxicity study	79 mg	51 weeks (3 times / week)	Mouse (female)	No carcinogenic effect		Literature

## 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Read-across

## trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	> 22000 mg/kg bw/day	52 week(s)	Mouse (male / female)	No carcinogenic effect		Read-across

## propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (dust)	NOAEC	OECD 453	5 mg/m <sup>3</sup> air	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect	Lungs	Experimental value
Oral (diet)	NOEL	Carcinogenic toxicity study	50000 ppm	103 weeks (7 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### WOODFILLER

No (test) data on the mixture available

Judgement is based on the relevant ingredients

## acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
	LOAEC	Equivalent to OECD 414	11000 mg/kg bw/day	14 days (gestation, daily)	Rat	Fetotoxicity	Foetus	Experimental value
Maternal toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	11000 ppm	14 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL		900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Literature

## n-butyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Fetotoxicity		Experimental value
Maternal toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Maternal toxicity		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	OECD 416	2000 ppm	> 90 day(s)	Rat (male / female)	No effect		Experimental value

## 2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation)	NOAEL	Equivalent to OECD 414	> 4000 ppm	10 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
Developmental toxicity (Inhalation (vapours))								
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	1500 ppm	10 days (gestation, daily)	Rat	No effect		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEL	OECD 416	300 ppm		Rat (male / female)	No effect		Read-across

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

16 / 26



# WOODFILLER

## butan-1-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (drinking water))	NOAEL	Equivalent to OECD 414	1454 mg/kg bw/day	21 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (drinking water))	NOAEL	Equivalent to OECD 414	1454 mg/kg bw/day	21 day(s)	Rat	No effect		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	OECD 416	2000 ppm		Rat (male / female)	No effect		Experimental value

## trizinc bis(orthophosphate)

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Developmental toxicity study	42.5 mg/kg bw/day	10 day(s)	Rat (female)	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	Developmental toxicity study	42.5 mg/kg bw/day	10 days (gestation, daily)	Rat (female)	No effect		Read-across
Effects on fertility (Oral (stomach tube))	NOAEL (F1)	Equivalent to OECD 416	15 mg/kg bw/day		Rat (male / female)	No effect		Read-across

## propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day	21 day(s) - 70 day (s)	Rat (male / female)	No effect		Experimental value

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	2 weeks (7 days / week)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	2 weeks (7 days / week)	Rat	No effect		Experimental value

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Toxicity other effects

#### WOODFILLER

Classification is based on the relevant ingredients  
acetone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study Skin

#### n-butyl acetate

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
NOEC	EPA OTS 798.6050	1500 ppm		Hypoactivity	6 h	Rat (male / female)	Experimental value
NOAEC	EPA OTS 798.6050	500 ppm		no neurotoxic effects	13 week(s)	Rat (male / female)	Experimental value

### Conclusion

Repeated exposure may cause skin dryness or cracking.

### Chronic effects from short and long-term exposure

#### WOODFILLER

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### WOODFILLER

No (test) data on the mixture available  
Classification is based on the relevant ingredients

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

17 / 26

# WOODFILLER

## acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	6210 mg/l - 8120 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	LC50		8800 mg/l	48 h	Daphnia pulex	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEC		530 mg/l		Algae		Fresh water	
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2212 mg/l	28 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value

## n-butyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	18 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	Equivalent to OECD 202	44 mg/l	48 h	Daphnia sp.	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	397 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; GLP
	NOEC	OECD 201	196 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; Growth rate
Long-term toxicity aquatic crustacea	NOEC	OECD 211	23.2 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; Reproduction
Toxicity aquatic micro-organisms	IC50	TETRATOX assay	356 mg/l	40 h	Tetrahymena pyriformis	Static system	Fresh water	Experimental value; Growth

	Parameter	Method	Value	Duration	Species	Value determination
Toxicity terrestrial plants	EC50	Equivalent to OECD 208	> 1000 mg/kg soil dw	14 day(s)	Lactuca sativa	Experimental value

## 2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	100 mg/l - 180 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	> 500 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	≥ 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 204	47.5 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; Behaviour
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC10	Equivalent to OECD 209	> 1000 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Respiration

## butan-1-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1376 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	1328 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	225 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	OECD 211	4.1 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC50	DIN 38412-8	4390 mg/l	17 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Growth

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

18 / 26

# WOODFILLER

## trizinc bis(orthophosphate)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	ASTM E729-88	0.169 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Read-across; Lethal
Acute toxicity crustacea	EC50	EPA 600/4-85/013	0.86 mg/l	48 h	Daphnia magna	Static system	Fresh water	Read-across; GLP
Toxicity algae and other aquatic plants	IC50	OECD 201	0.136 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	0.024 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 215	0.199 mg/l	30 day(s)	Oncorhynchus mykiss	Flow-through system	Fresh water	Read-across; Lethal
Long-term toxicity aquatic crustacea	NOEC		0.035 mg/l	3 week(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; Reproduction
Toxicity aquatic micro-organisms	IC50	ISO 9509:2006	0.35 mg/l	4 h	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

## propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC		2344 µmol/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		> 1000 mg/l		Pisces		Fresh water	
Acute toxicity crustacea	EC50		> 1000 mg/l		Invertebrata		Fresh water	
Toxicity algae and other aquatic plants	EC50	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate

## Conclusion

Harmful to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

### acetone

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90.9 %	28 day(s)	Experimental value

### n-butyl acetate

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	83 %; Oxygen consumption	28 day(s)	Experimental value

### 2-methoxy-1-methylethyl acetate

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	83 %; Oxygen consumption	28 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	10.818 h	1.5E6 /cm <sup>3</sup>	Calculated value

#### Biodegradation soil

Method	Value	Duration	Value determination
Equivalent to OECD 304A	> 57 %; GLP	1 day(s)	Experimental value

# WOODFILLER

## butan-1-ol

### Biodegradation water

Method	Value	Duration	Value determination
APHA	92 %; Oxygen consumption	20 day(s)	Experimental value

### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	18.629 h	1.5E6 /cm <sup>3</sup>	Calculated value

## propan-2-ol

### Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

## Conclusion

### Water

Contains non readily biodegradable component(s)

## 12.3. Bioaccumulative potential

### WOODFILLER

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

## acetone

#### Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.23		Test data

## n-butyl acetate

#### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.3	25 °C	Experimental value

## 2-methoxy-1-methylethyl acetate

#### Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		1.2	20 °C	Experimental value

## butan-1-ol

### BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	3.162 l/kg; Fresh weight			Calculated value

#### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		1	25 °C	Experimental value

## trizinc bis(orthophosphate)

### BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF		116 - 60960; Fresh weight	21 day(s)	Gammarus sp.	Read-across

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (inorganic)			

## propan-2-ol

#### Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

## Conclusion

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

### acetone

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.374 - 0.988	Calculated value

# WOODFILLER

## n-butyl acetate

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.268 - 1.844	Calculated value

## 2-methoxy-1-methylethyl acetate

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.602 - 1.079	Calculated value

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	10.22 %	0 %	0.02 %	0.03 %	89.73 %	Calculated value

## butan-1-ol

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.54	Calculated value

## **Conclusion**

Contains component(s) with potential for mobility in the soil

## **12.5. Results of PBT and vPvB assessment**

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## **12.6. Endocrine disrupting properties**

No evidence of endocrine disrupting properties

## **12.7. Other adverse effects**

## WOODFILLER

### **Greenhouse gases**

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### **Ozone-depleting potential (ODP)**

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

### **Groundwater**

Groundwater pollutant

#### acetone

##### **Groundwater**

Groundwater pollutant

#### n-butyl acetate

##### **Groundwater**

Groundwater pollutant

#### 2-methoxy-1-methylethyl acetate

##### **Groundwater**

Groundwater pollutant

#### butan-1-ol

##### **Groundwater**

Groundwater pollutant

#### trizinc bis(orthophosphate)

##### **Groundwater**

Groundwater pollutant

#### propan-2-ol

##### **Groundwater**

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### **13.1. Waste treatment methods**

#### **13.1.1 Provisions relating to waste**

##### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11\* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### **13.1.2 Disposal methods**

# WOODFILLER

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

## 13.1.3 Packaging/Container

### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Hazard identification number	
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Hazard identification number	23
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Inland waterways (ADN)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

22 / 26

# WOODFILLER

Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
79.58 %	
677.6 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC and 2009/161/EU)

2-methoxy-1-methylethyl acetate

Product name	Skin resorption
2-Methoxy-1-methylethylacetate	Skin

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

23 / 26

# WOODFILLER

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> <li>· acetone</li> <li>· n-butyl acetate</li> <li>· 2-methoxy-1-methylethyl acetate</li> <li>· butan-1-ol</li> <li>· propan-2-ol</li> </ul>	<p>Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<ol style="list-style-type: none"> <li>1. Shall not be used in: <ul style="list-style-type: none"> <li>— ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,</li> <li>— tricks and jokes,</li> <li>— games for one or more participants, or any article intended to be used as such, even with ornamental aspects,</li> </ul> </li> <li>2. Articles not complying with paragraph 1 shall not be placed on the market.</li> <li>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: <ul style="list-style-type: none"> <li>— can be used as fuel in decorative oil lamps for supply to the general public, and,</li> <li>— present an aspiration hazard and are labelled with H304,</li> </ul> </li> <li>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</li> <li>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: <ol style="list-style-type: none"> <li>a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</li> <li>b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</li> <li>c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</li> </ol> </li> <li>6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public.</li> <li>7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</li> </ol>
<ul style="list-style-type: none"> <li>· acetone</li> <li>· n-butyl acetate</li> <li>· 2-methoxy-1-methylethyl acetate</li> <li>· butan-1-ol</li> <li>· propan-2-ol</li> </ul>	<p>Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<ol style="list-style-type: none"> <li>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: <ul style="list-style-type: none"> <li>— metallic glitter intended mainly for decoration,</li> <li>— artificial snow and frost,</li> <li>— "whoopee" cushions,</li> <li>— silly string aerosols,</li> <li>— imitation excrement,</li> <li>— horns for parties,</li> <li>— decorative flakes and foams,</li> <li>— artificial cobwebs,</li> <li>— stink bombs.</li> </ul> </li> <li>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: <p>"For professional users only".</p> </li> <li>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</li> <li>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</li> </ol>

## National legislation Belgium

### WOODFILLER

No data available

#### 2-methoxy-1-methylethyl acetate

Résorption peau	Acétate de 2-(1-méthoxy)propyle; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

#### butan-1-ol

Résorption peau	Alcool n-butylique; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	---

## National legislation The Netherlands

### WOODFILLER

Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

SZW - Lijst van kankerverwekkende stoffen	Als kankerverwekkende stof ingedeeld in categorie 1A of 1B als bedoeld in bijlage I van de Verordening (EG) nr. 1272/2008 van het Europees parlement en de Raad van 16 december 2008; Listed in SZW-list of carcinogenic substances
---	---

## National legislation France

### WOODFILLER

No data available

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

24 / 26



# WOODFILLER

## 2-methoxy-1-methylethyl acetate

Risque de pénétration percutanée	Acétate de 2-méthoxy-1-méthyléthyle; PP
----------------------------------	---

### National legislation Germany

#### WOODFILLER

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

#### acetone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

#### n-butyl acetate

TA-Luft	5.2.5/I
TRGS900 - Risiko der Fruchtschädigung	n-Butylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

## 2-methoxy-1-methylethyl acetate

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	2-Methoxy-1-methylethylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

#### butan-1-ol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Butan-1-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

#### trizinc bis(orthophosphate)

TA-Luft	5.2.1
---------	-------

#### propan-2-ol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

TA-Luft	5.2.1
---------	-------

### National legislation United Kingdom

#### WOODFILLER

No data available

## 2-methoxy-1-methylethyl acetate

Skin absorption	1-Methoxypropyl acetate; Sk
-----------------	-----------------------------

#### butan-1-ol

Skin absorption	Butan-1-ol; Sk
-----------------	----------------

### Other relevant data

#### WOODFILLER

No data available

#### acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

#### propan-2-ol

IARC - classification	3; Isopropanol
TLV - Carcinogen	2-propanol; A4

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

IARC - classification	2B; Titanium dioxide
TLV - Carcinogen	Titanium dioxide; A4

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under heading 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Reason for revision: 3.2; 9; 12; 15

Publication date: 2011-07-08

Date of revision: 2020-11-25

Revision number: 0300

Product number: 51293

25 / 26

# WOODFILLER

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ERC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.