



# Al-Fix Filler

FILLER FOR AL-FIX GLUES

- ✓ To obtain an easy volume for the use of Al-Fix glues.
- ✓ To fill damages and bondings where a gap/opening between the materials is required.
- ✓ Powder in handy dispensing bottle.

## Technical Info

- Base: e.g. glass.
- Form: powder.
- Colour: white.
- Odour: odourless.
- Flammability: not flammable.
- Relative density at 20°C: 2,6.
- Shelf life: 36 months, dry and cool.
- Safety measures: consult the Safety Data Sheet.

## Packing

Al-Fix Filler - bottle 20ml

501100000

## Product [AFI]

### Characteristics

Al-Fix is an adhesive which bonds in seconds and has a special formula based on Cyanacrylate. Al-Fix Filler is a one component adhesive which is solventless and consists mainly of Athyl Cyanacrylate Monomer. Al-Fix is temperature resistant in the range from -30°C to +100°C. Al-Fix is resistant to solvents, oils, benzene, temperature fluctuations and atmospheric conditions. Al-Fix Filler joints have a high tensile shear strength and show no shrinkage.

## Use

- Apply in layers: Spread Al-Fix adhesive and then Al-Fix Filler.
- Repeat if necessary.

If desired, accelerate curing with the help of Al-Fix Aktivator.