SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



PENETRON AEROSOL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: PENETRON AEROSOL Product name **Registration number REACH** : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Lubricant

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*

Industrielaan 5B

B-2250 Olen

2 +32 14 25 76 40

⊞ +32 14 22 02 66

info@novatio.be

*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements







Contains: Kerosine (petroleum), hydrodesulfurized.

Signal wo	ord	Da
H-statem	ents	

Extremely flammable aerosol. H222

H229 Pressurised container: May burst if heated.

Causes skin irritation. H315

May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

P-statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Revision number: 0700

Reason for revision: 3.2, 8, 12

Publication date: 2000-05-17 Date of revision: 2021-06-19

BIG number: 32074

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves, protective clothing and eye protection/face protection.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	lRemark	M-factors and ATE
Kerosine (petroleum), hydrodesulfurized 01-2119462828-25	64742-81-0 265-184-9	C≤40%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent	
butane	106-97-8 203-448-7	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	

- (1) For H- and EUH-statements in full: see section 16
- (2) Substance with a Community workplace exposure limit
- (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006
- (21) 1,3-butadiene < 0.1%

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Headache. Dizziness. Drowsiness.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17

Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 2 / 12

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Protect against frost. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 3 / 12

Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m ³
Carburant pour les moteurs à réaction (en vapeur d' hydrocarbure total) : application limitée aux conditions d'exposition aux aérosols négligeable	Time-weighted average exposure limit 8 h	200 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

France

Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
,	1900 mg/m³

Germany

Germany		
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³
Propan	Time-weighted average exposure limit 8 h (TRGS 900) 1000 ppm	
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³

UK

Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m ³
Short time value (Workplace exposure limit (EH40/2005))	750 ppm
Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m³

USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
Kerosene/Jet fuels, as total hydrocarbon vapor	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 mg/m³ (P)

⁽P): Application restricted to conditions in which there are negligible aerosol exposures

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

If applicable and available it will be listed below.

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 4 / 12

Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	0.7 - 9.5 % ; Propellant
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	Not applicable (aerosol)
Boiling point	140 °C - 250 °C ; Liquid
Relative vapour density	No data available in the literature
Vapour pressure	8530 hPa ; 20 °C ; Propellant
Solubility	Water; insoluble
Relative density	0.84 ; 20 °C ; Liquid
Absolute density	844 kg/m³ ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
рН	Not applicable (non-soluble in water)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

PENETRON AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 420	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5.28 mg/l air	4 h	Rat (male / female)	Read-across	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

PENETRON AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17 Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 5 / 12

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Result	Method	Exposure time	Time point	-	Value determination	Remark
Eye	Not irritating	EPA OTS 798.4500			Rabbit	Read-across	
Skin	Irritating		24 h	24; 48; 72 hours	Rabbit	Read-across	

Conclusion

Causes skin irritation.

Not classified as irritating to the respiratory system

Not classified as irritating to the eyes

Respiratory or skin sensitisation

PENETRON AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		Guinea pig (male)	Read-across	

Conclusion

Not classified as sensitizing for inhalation Not classified as sensitizing for skin

Specific target organ toxicity

PENETRON AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 408	750 mg/kg bw/day		No effect	21 week(s)	Rat (female)	Read-across
Dermal	NOAEL	Equivalent to OECD 411	≥ 495 mg/kg bw/day		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	> 1000 mg/m³ air		No effect	90 days (continuous)	Rat (female)	Read-across
Inhalation			STOT SE cat.3		Drowsiness, dizziness			Literature study

Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

Mutagenicity (in vitro)

PENETRON AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	Equivalent to OECD 476	Mouse (lymphoma L5178Y	No effect	Read-across	
activation, negative		cells)			
without metabolic					
activation					

Mutagenicity (in vivo)

PENETRON AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Result	Method	Exposure time	Test substrate	Organ	Value determination
Ambiguous (Intraperitoneal)	Equivalent to OECD		Mouse (male / female)		Read-across
	479				

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

PENETRON AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 6 / 12

Kerosine (petroleum), hydrodesulfurized

Route of Para exposure	ameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal		Equivalent to OECD 451		104 week(s)		Tumor formation	Skin	Read-across

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

PENETRON AEROSOL

No (test)data on the mixture available Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Read-across
	LOAEL	OECD 414	1500 mg/kg bw/day	10 day(s)	Rat	Reduced foetal bodyweights	Foetus	Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	500 mg/kg bw/day	10 day(s)	Rat	No effect		Read-across
	LOAEL	OECD 414	1000 mg/kg bw/day	10 day(s)	Rat	Body weight reduction		Read-across
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 415	≥ 1500 mg/kg bw/day	21 week(s)	Rat (female)	No effect		Read-across
	NOAEL	Equivalent to OECD 415	≥ 3000 mg/kg bw/day	10 week(s) - 13 week(s)	Rat (male)	No effect		Read-across

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

PENETRON AEROSOL

No (test)data on the mixture available

Chronic effects from short and long-term exposure

PENETRON AEROSOL

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

PENETRON AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	2 mg/l - 5 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	1.4 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	1 mg/l - 3 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Cell numbers
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	0.48 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 7 / 12

Kerosine (petroleum), hydrodesulfurized

Biodegradation water

_	Diouchiadation water							
	Method	Value	Duration	Value determination				
	OECD 301F	58.6 %	28 day(s)	Experimental value				

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

PENETRON AEROSOL

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

Kerosine (petroleum), hydrodesulfurized

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

No (test)data on mobility of the component(s) available

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

PENETRON AEROSOL

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Kerosine (petroleum), hydrodesulfurized

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 08* (waste engine, gear and lubricating oils: other engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1	. UN number					
	UN number	1950				
14.2	14.2. UN proper shipping name					
	Proper shipping name	aerosols				

14.3. Transport hazard class(es)

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 8 / 12

PENE	TRON AEROSOL
Hazard identification number	
Class	2
Classification code	5F
4.4. Packing group	
Packing group	
Labels	2.1
4.5. Environmental hazards	
Environmentally hazardous substance mark	yes
4.6. Special precautions for user	- Iraa
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
(RID)	
4.1. UN number	lean
UN number	1950
4.2. UN proper shipping name	I-
Proper shipping name	aerosols
4.3. Transport hazard class(es)	100
Hazard identification number	23
Class	2
Classification code	5F
4.4. Packing group	
Packing group	
Labels	2.1
4.5. Environmental hazards	I
Environmentally hazardous substance mark	yes
.4.6. Special precautions for user	100
Special provisions	190 327
Special provisions	344
Special provisions	
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
nd waterways (ADN)	
4.1. UN number	T
UN number	1950
4.2. UN proper shipping name	
Proper shipping name	aerosols
4.3. Transport hazard class(es)	la la
Class	2
Classification code	5F
.4.4. Packing group	
Packing group	2.4
Labels	2.1
4.5. Environmentally hazardays substance mark	luge
Environmentally hazardous substance mark	yes
4.6. Special prevarious	100
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
(IMDG/IMSBC)	
4.1. UN number	
UN number	1950
4.2. UN proper shipping name	
Proper shipping name	aerosols
4.3. Transport hazard class(es)	L.
Class	2.1
4. <u>4</u> . Packing group	
Packing group	
Labels	2.1
	2.1 P

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 9 / 12

Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instrume	ents
Annex II of MARPOL 73/78	Not applicable
Air (ICAO-TI/IATA-DGR)	
14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	

SECTION 15: Regulatory information

Environmentally hazardous substance mark

Limited quantities: maximum net quantity per packaging

14.6. Special precautions for user

Passenger and cargo transport

Special provisions
Special provisions

Special provisions

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
0 % - 80 %	
672 g/l	

yes

A145

A167

A802

30 kg G

Ingredients according to Regulation (EC) No 648/2004 and amendments

 $\geq \! \! 30\% \text{ aliphatic hydrocarbons, } \! \geq \! \! 30\% \text{ aromatic hydrocarbons, perfumes, limonene, cinnamal}$

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain dangerous substances, mixtures and articles.		
	Designation of the substance, of the group of	Conditions of restriction
	substances or of the mixture	
· Kerosine (petroleum), hydrodesulfurized	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 10 / 12

		c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· Kerosine (petroleum), hydrodesulfurized	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation Belgium

PENETRON AEROSOL

No data available

Kerosine (petroleum), hydrodesulfurized

Résorption peau	Carburant pour les moteurs à réaction (en vapeur d'hydrocarbure total) : application limitée aux conditions d'exposition
	aux aérosols négligeable; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux,
	constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par
	présence de l'agent dans l'air.

National legislation The Netherlands

PENETRON AEROSOL

Waterbezwaarlijkheid Z (2); Algemene Beoordelingsmethodiek (ABM)

National legislation France

PENETRON AEROSOL

No data available

National legislation Germany PENETRON AEROSOL

	Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
	WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
<u>K</u>	Kerosine (petroleum), hydrodesulfurized	
	TA-Luft	5.2.5

National legislation United Kingdom

PENETRON AEROSOL

No data available

Other relevant data

PENETRON AEROSOL

No data available

Kerosine (petroleum), hydrodesulfurized

TLV - Skin absorption	Kerosene/Jet fuels, as total hydrocarbon vapor; Skin; Danger of cutaneous absorption
TLV - Carcinogen	Kerosene/Jet fuels, as total hydrocarbon vapor; A3

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

 $\ensuremath{\mathsf{H411}}\xspace$ Toxic to aquatic life with long lasting effects.

(*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level ATE **Acute Toxicity Estimate**

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17

Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 11 / 12

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2, 8, 12 Publication date: 2000-05-17
Date of revision: 2021-06-19

Revision number: 0700 BIG number: 32074 12 / 12