SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830



XPR-90

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: XPR-90Registration number REACH: Not applProduct type REACH: Mixture

: Not applicable (mixture)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Manufacturer of the product

Novatech International N.V. Industrielaan 5B B-2250 Olen ☎ +32 14 85 97 37 ➡ +32 14 85 97 38 info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) : +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

2.2. Label elements

.2. Eaber cicilients		
Contains: hydrocarbor	ns, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics.	
Signal word	Danger	
H-statements		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	
H336	May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effect	S.
P-statements		
P210	Keep away from heat, hot surfaces, sparks, op	en flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition	on source.
P251	Do not pierce or burn, even after use.	
P261	Avoid breathing spray.	
ed by: Brandweerinformatie	ecentrum voor gevaarlijke stoffen vzw (BIG)	Publication date: 2010-07-09
nische Schoolstraat 43 A, B-2	2440 Geel	Date of revision: 2019-06-26
H222 H229 H336 H412 P-statements P210 P211 P251 P251 P261	Pressurised container: May burst if heated. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effect Keep away from heat, hot surfaces, sparks, op Do not spray on an open flame or other ignitio Do not pierce or burn, even after use. Avoid breathing spray.	pen flames and other ignition sources. No sm on source. Publication date: 2010-07-09

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (B Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be © BIG vzw Reason for revision: 3

Revision number: 0400

134-16239-660-en

P304 + P340 P410 + P412 Supplemental information EUH066 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119471843-32	927-241-2		Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412	(1)(10)	UVCB
propane 01-2119486944-21	74-98-6 200-827-9		Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
butane 01-2119474691-32	106-97-8 203-448-7		Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Do not apply (chemical) neutralizing agents without medical advice. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Do not apply (chemical) neutralizing agents without medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation: Central nervous system depression. Narcosis. After skin contact: ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin. After eye contact: No effects known. After ingestion: No effects known. 4.2.2 Delayed symptoms No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

5.1.2 Unsuitable extinguishing media:

Reason for revision: 3

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam. Major fire: Water (water can be used to control jet flame), Foam.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1- C3)	Time-weighted average exposure limit 8 h	1000 ppm
	Short time value	980 ppm
	Short time value	2370 mg/m³

France

Reason for revision: 3

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m ³
Germany		
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³
UK		
Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m³
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m ³
USA (TLV-ACGIH)		
Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
· · · · ·		
h) National hiological limit values		
b) National biological limit values If limit values are applicable and available	these will be listed below.	

8.1.4 Threshold values

DNEL/DMEL - Workers hydrocarbons C9-C10 n-alkanes isoalkanes cyclics < 2% aromatics hvdroc

Effect level (DNEL/DMEL)	Туре	Value	Remark				
DNEL Long-term systemic effects inhalation		871 mg/m³					
	Long-term systemic effects dermal	77 mg/kg bw/day					

DNEL/DMEL - General population

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Effect level (DNEL/DMEL) Type		Value	Remark
DNEL	Long-term systemic effects inhalation	185 mg/m³	
	Long-term systemic effects dermal	46 mg/kg bw/day	
	Long-term systemic effects oral	46 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).							
	Measured breakthrough time	Remark	Protection index				
nitrile rubber	> 480 minutes	0.35 mm	Class 6				

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour
Particle size	Not applicable (mixture)

Reason for revision: 3

Publication date: 2010-07-09 Date of revision: 2019-06-26

Explosion limits	0.8 - 9.5 vol %	
Flammability	Extremely flammable aerosol.	
Log Kow	Not applicable (mixture)	
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid	
Kinematic viscosity	1 mm²/s ; 40 °C ; Liquid	
Melting point	No data available	
Boiling point	-45 °C - 165 °C ; Liquid	
Evaporation rate	0.56 ; Butyl acetate ; Liquid	
Relative vapour density	> 1	
Vapour pressure	8530 hPa ; 20 °C	
Solubility	Water ; insoluble	
Relative density	0.75 ; 20 °C ; Liquid	
Decomposition temperature	No data available	
Auto-ignition temperature	No data available	
Flash point	No data available	
Explosive properties	No chemical group associated with explosive properties	
Oxidising properties	No chemical group associated with oxidising properties	
рН	No data available	

9.2. Other information

Absolute density	750 kg/m³ ; 20 °C ; Liquid

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

XPR-90

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw		Rabbit (male / female)	Experimental value	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5.6 mg/l air		Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

XPR-90

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3

Publication date: 2010-07-09 Date of revision: 2019-06-26

Revision number: 0400

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Еуе		Equivalent to OECD 405		1; 24; 48; 72; 168 hours	Rabbit	Read-across	Single treatment
Skin		Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Respiratory or skin sensitisation

XPR-90

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark
				point			
Skin	Not sensitizing	Equivalent to OECD 406		,	Guinea pig (female)	Read-across	

Conclusion

Not classified as sensitizing for skin

Specific target organ toxicity

XPR-90

No (test)data on the mixture available

Classification is based on the relevant ingredients

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	· · · · · ·	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	> 1000 mg/kg bw/day		No effect		Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400 mg/m³ air			13 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation			STOT SE cat.3		Drowsiness, dizziness			Literature study

Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

Mutagenicity (in vitro)

XPR-90

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

Conclusion

Not classified for mutagenic or genotoxic toxicity

Mutagenicity (in vivo)

XPR-90

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD	5 days (6h / day)	Rat (male / female)		Read-across
	478				

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

XPR-90

No (test)data on the mixture available

Reason for revision: 3

Publication date: 2010-07-09 Date of revision: 2019-06-26

Revision number: 0400

201

Judgement is based on the relevant ingredients

rocarbons, C9	-C10, n-alkane	s, isoalkanes, cyclic	s, < 2% aromatics					
Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determinatio
Inhalation	NOAEC	Equivalent to	≥ 2200 mg/m³	105 weeks (6h / day,	Rat (female)	No carcinogenic		Read-across
(vapours)		OECD 453	air	5 days / week)		effect		

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

XPR-90

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	1-0-	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	≥ 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	> 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Read-across
Effects on fertility	NOAEL	Equivalent to OECD 413		14 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Read-across

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

XPR-90

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
				Skin dryness or cracking		Literature study Skin

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

XPR-90

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

XPR-90

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	10 mg/l - 30 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	22 mg/l - 46 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOEL	OECD 201	< 1 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEL		0.182 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		0.317 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Nominal concentration

Conclusion

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Reason for revision: 3

Publication date: 2010-07-09 Date of revision: 2019-06-26

Revision number: 0400

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation water

louegradation water				
Method	Value	Duration	Value determination	
OECD 301F: Manometric Respirometry Test	89 %	28 day(s)	Experimental value	
			-	
hototransformation air (DT50 air)				
Method	Value	Conc. OH-radicals	Value determination	
AOPWIN v1.92	18.679 h	1.5E6 /cm³	Calculated value	
	Method OECD 301F: Manometric Respirometry Test hototransformation air (DT50 air) Method	Method Value OECD 301F: Manometric Respirometry Test 89 % hototransformation air (DT50 air) Value Method Value	Method Value Duration OECD 301F: Manometric Respirometry Test 89 % 28 day(s) hototransformation air (DT50 air) Value Conc. OH-radicals	

Conclusion

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

XPR-90

Log Kow

Not applicable (mixture)	Method	Remark	Value	Temperature	Value determination
		Not applicable (mixture)			

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

BCF fishes								
Parameter	Method		Value	Duration	Species			Value determination
BCF	BCFBAF v3	.01	551.7 l/kg; Fresh					Estimated value
			weight					
Log Kow								
Method		Remark		Value		Temperature	Va	lue determination
				4.66			Exp	perimental value

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter				Method			Value		Value determination
log Koc				SRC PCK	OCWIN v2.0		2.380		Calculated value
Percent distribution									
Method	Fraction air	Fraction biota	Fraction		Fraction soil	Fraction	water	Value determi	ination
			sediment	t					
Fugacity Model	34.9 %		0.553 %		1.19 %	63.4 %		Calculated value	ue
Level III									

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

XPR-90

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point. **13.1.3 Packaging/Container**

European Union

Reason for revision: 3

Waste material code packaging (Directive 2008/98/EC). 15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14. <u>1. UN number</u>	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

1950
Aerosols
23
2
5F
2.1
no
190
327
344
625
Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14. <u>1. UN number</u>	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

Reason for revision: 3

UN number	1950
4.2. UN proper shipping name	
Proper shipping name	aerosols
4.3. Transport hazard class(es)	
Class	2.1
4.4. Packing group	
Packing group	
Labels	2.1
4.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
4.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
4.7. Transport in bulk according to Annex II of Marpol and the	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14. <u>1</u> . UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14. <u>4. Packing group</u>	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
European legislation:

VOC content Directive 2010/75/EU

[VOC content	Remark
	100 %	
	695 g/l	

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
 hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics 	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic	 Shall not be used in: ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
Reason for revision: 3		Publication date: 2010-07-09

Date of revision: 2019-06-26

Revision number: 0400

Product number: 49027

	XPR	
	effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopte by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shat ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibl and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legib and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agenc to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled H304, intende for supply to the general public. 7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled H304 to the competent authorit in the Member State concerned. Member States shall make those data available to the Commission.'
hydrocarbons, C9-C10, n-alkanes, soalkanes, cyclics, < 2% aromatics	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	 Shall not be used, as substance or as mixtures in aerosol dispensers where these aeroso dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: metallic glitter intended mainly for decoration, artificial snow and frost, "whoopee" cushions, silly string aerosols, imitation excrement, decorative flakes and foams, artificial cobwebs, stink bombs. Without prejudice to the application of other Community provisions on the classification packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
<u>National legislation Belgium</u> <u>XPR-90</u> No data available <u>National legislation The Netherl</u> XPR-90	ands	
Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodie	k (ABM)
National legislation France XPR-90		
<u>XPR-90</u> No data available		
National legislation Germany XPR-90		
WGK	2. Vorordnung über Anlagen zum Limge	ang mit wassergefährdenden Stoffen (AwSV) - 18 Anril 2017

 WGK
 2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

 hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics</td>
 5.2.5/1

TA-Luft

National legislation United Kingdom

No data available

Other relevant data

XPR-90

No data available

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 3

Publication date: 2010-07-09 Date of revision: 2019-06-26

Product number: 49027

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3