novatio



Multispray

AGAINST RUST, DAMP, MOISTURE AND LEAKAGE CURRENTS

- Superfast acting.
- Works by cold shrinkage.
- Colourless and practically odour-free.
- 360° spray direction.

Technical Info

- Based on mineral oil.
- Colour: colourless.
- Odour: characteristic.
- Water solubility: insoluble.
- Density at 20°C: 0.811.
- Partial pressure: 8,53 bar.
- Boiling point: 187 300°C.
- Relative density at 20°C: 0.81g.
- Temperature resistance: -80°C to +190°C.
- Dynamic viscosity at 20°C: 1 mPa.s.
- Kinematic viscosity at 20°C: 1 mPa.s.
- Storage life: 36 months if kept dry, cool and frost-free.
- Safety measures: Please consult the safety card.

PackingMultispray - aerosol 600ml236116000Multispray - aerosol 100ml236101000

Use

- Shake well before use.
- Spray and briefly allow to penetrate.
- If necessary, allow the propellant gasses to evaporate.

Product [MUS]

Characteristics

- Is fast and effective in contact with rust, tar, grease and water and combines penetrating power, lubrication, protection, cleaning, rust removal, drives away moisture and the cold shrinkage results in time saving.
- Contains no silicones and is safe to use on plastics, lacquers







■ novatio

Novatio is a registered trademark of Novatech International nv. |Industrielaan 5B - B-2250 Olen - Belgium |Tel:+32-14-85 97 37 |Fax: + 32-14-85 97 38 ISO CERTIFIED COMPANY ISO 9001: 2008 - ISO 14001: 2004 - OHSAS 18001: 2007