

# Stripfix



TRANSPARENT GLUE ON ROLL WITH IMMEDIATE ADHESIVE POWER

- ✓ Direct adhesion up to 8 kg / cm<sup>2</sup>.
- ✓ Good chemical resistance.
- ✓ Does not dry, does not harden.
- ✓ Can also be used to seal.

## Technical Info

- Composition: rubber / resin.
- Elongation: 1000%.
- Initial adhesive strength: 52 N/cm<sup>2</sup>.
- Tensile strength: 60 N/cm<sup>2</sup> after 10 min.; 80 N/cm<sup>2</sup> after 24 hours.
- Application weight: 405 g/m<sup>2</sup>.
- Temperature resistance: -10°C to +50°C.
- Static shear FTM8: 0,5kg -25mm x 25mm/+20°C.
- Application temperature: > +10°C.
- Water absorption: 0%.
- Thickness: 0,4 mm.
- Pressure needed to achieve 20% compression: 1,6 kg/cm<sup>2</sup>.
- U.V. resistance: bad - exposure to UV light should be avoided.
- Tolerance: thickness and width < 10%.
- Shelf life: 36 months, keep dry, cool and frost-proof.

## Packing

Stripfix - roll 12mm / 0,4mm / 30m	521208000
Stripfix - roll 19mm / 0,4mm / 30m	521908000

## Product [SFX]

### Characteristics

- A synthetic, pressure-sensitive transparent adhesive on roll. It has been designed to provide a very strong bond between a wide variety of materials and substrates.
- Can be used immediately on clean, dry and grease-proof surfaces.
- Is excellent for bonding "difficult" materials such as glass, metal, wood, rubber and plastics including polyethylene.

### Applications

Building: mounting of connections for protective plates of drain pipes, insulating material in polypropylene, filter membranes for road construction; bonding of light insulating plates, connections in synthetic material,....

Furniture industry: mounting of laminated decorative frames and fixing of corners on furniture.

Car industry: fixing of insulating material, name-plates and signs,....

Construction: bonding of side and roof panels on caravans.

## Use

Apply on dry and clean surface.

If necessary, first clean with Safety Clean and / or Multifoam.

Press firmly.