

Woodfiller

SPRAY WOOD FILLER WITH HIGH COVERAGE

- ✓ Excellent filling qualities.
- ✓ Wet-to-wet application possible.
- ✓ To fill up pores, nerves and irregularities.



Technical Info

- Colour: Yellow - beige.
- Odour: Specific.
- Vapour pressure at 20 °C (68 °F): 3500 hPa (2625 mm Hg).
- Density at 20 °C (68 °F): 0.885 g/cm³.
- Solubility in water: None Mixability in water.
- Poor Organic solvent: 74,9% EU VOC 662,8 g/l EU VOC in % 74,89%.
- Level of fixed substances: 18,8% Filler strength: +/- 50 microns.
- Storage life: 120 months, dry, cool and frost-free
Safety measures: Please consult the safety data sheet

Packing

Woodfiller - aerosol 400ml

120935000

Product [WFI]

Characteristics

Woodfiller is a spray finishing filler with a high coverage to cover up small irregularities. Bonds well on sanded wood and derivatives. Woodfiller is also perfect to use on small, localised damaged spots. The adjustable nozzle makes this aerosol usable as a spray gun, as it has width and flow adjustment in the head.

Use

- The surface to be treated must be grease-free, clean, dry and sanded.
- Shake the aerosol properly for two minutes and try on a test surface.
- Let the first coating absorbed for 12 to 15 minutes before applying a second coating (at 20 °C).

Filling must be done beforehand, as Woodfiller is be used as a spray finishing filler.

Treat difficult and oil-absorbent wood types first with Seal&Bond Woodprimer.