

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

TRIMFIX WT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : TRIMFIX WT
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Adhesive

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Carc.	category 2	H351: Suspected of causing cancer.
Skin Irrit.	category 2	H315: Causes skin irritation.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

2.2. Label elements



Contains: dichloromethane; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane.

Signal word Danger

H-statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H351	Suspected of causing cancer.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

TRIMFIX WT

H412 Harmful to aquatic life with long lasting effects.

P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves, protective clothing and eye protection/face protection.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

May build up electrostatic charges: risk of ignition
Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
dichloromethane 01-2119480404-41	75-09-2 200-838-9	30% ≤C≤60%	Carc. 2; H351 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(6)(10)	Constituent	
petroleum gases, liquefied	68476-85-7 270-704-2	30% ≤C≤60%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane 01-2119475514-35	921-024-6	1%≤C≤5%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dizziness. Drowsiness. EXPOSURE TO HIGH CONCENTRATIONS: Nausea. Headache. Disturbances of consciousness. Central nervous system depression.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

2 / 16

TRIMFIX WT

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (hydrogen chloride, carbon monoxide - carbon dioxide). Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe strict hygiene.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

Aluminium, viton, PVC.

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

TRIMFIX WT

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Methylene chloride; Dichloromethane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	100 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	353 mg/m ³
	Short time value (Indicative occupational exposure limit value)	200 ppm
	Short time value (Indicative occupational exposure limit value)	706 mg/m ³

Belgium

Chlorure de méthylène	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	177 mg/m ³
	Short time value	200 ppm
	Short time value	706 mg/m ³
Pétrole (gaz liquéfié)	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1826 mg/m ³

The Netherlands

Methyleenchloride/ dichloormethaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	353 mg/m ³
	Short time value (Public occupational exposure limit value)	200 ppm
	Short time value (Public occupational exposure limit value)	706 mg/m ³
Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m ³

France

Dichlorométhane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	178 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	356 mg/m ³

Germany

Dichlormethan	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m ³

Austria

Dichlormethan (R 30)	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	175 mg/m ³
	Kurzzeitwert 30(Miw) 2x (MAK)	200 ppm
	Kurzzeitwert 30(Miw) 2x (MAK)	700 mg/m ³

UK

Dichloromethane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	100 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	353 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	706 mg/m ³
Liquefied petroleum gas	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1000 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1750 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1250 ppm
	Short time value (Workplace exposure limit (EH40/2005))	2180 mg/m ³

USA (TLV-ACGIH)

Dichloromethane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
-----------------	--	--------

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

4 / 16

TRIMFIX WT

Dichlormethan (Dichlormethan)	Vollblut: unmittelbar nach exposition	500 µg/l	
UK			
Dichloromethane (carbon monoxide)	End-tidal breath: post shift	30 ppm	
USA (BEI-ACGIH)			
Dichloromethane (Dichloromethane)	urine: end of shift	0,3 mg/L	Semi-quantative
Methemoglobin inducers (Methemoglobin)	Blood: during or end of shift	5 % of hemoglobin	Background, Nonspecific

8.1.2 Sampling methods

Product name	Test	Number
Methylene chloride (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Methylene chloride (Volatile Organic compounds)	NIOSH	2549
Methylene Chloride	NIOSH	1005
Methylene Chloride	OSHA	59
Methylene Chloride	OSHA	80

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

dichloromethane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	176 mg/m ³	
	Long-term systemic effects dermal	12 mg/kg bw/day	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2035 mg/m ³	
	Long-term systemic effects dermal	773 mg/kg bw/day	

DNEL/DMEL - General population

dichloromethane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	44 mg/m ³	
	Long-term systemic effects dermal	5.82 mg/kg bw/day	
	Long-term systemic effects oral	0.06 mg/kg bw/day	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	608 mg/m ³	
	Long-term systemic effects inhalation	699 mg/kg bw/day	
	Long-term systemic effects oral	699 mg/kg bw/day	

PNEC

dichloromethane

Compartment	Value	Remark
Fresh water	0.31 mg/l	
Marine water	0.031 mg/l	
Fresh water (intermittent releases)	0.27 mg/l	
Marine water (intermittent releases)	0.027 mg/l	
STP	26 mg/l	
Fresh water sediment	2.57 mg/kg sediment dw	
Marine water sediment	0.26 mg/kg sediment dw	
Soil	0.33 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe strict hygiene. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
viton	> 120 minutes	0.7 mm	Class 4	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

5 / 16

TRIMFIX WT

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Hydrocarbon odour
Odour threshold	No data available in the literature
Colour	Amber
Particle size	Not applicable (aerosol)
Explosion limits	1.4 - 10.9 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	50 mPa.s - 150 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	40 mm ² /s - 130 mm ² /s ; 20 °C ; Liquid
Melting point	Not applicable (aerosol)
Boiling point	No data available in the literature
Relative vapour density	No data available in the literature
Vapour pressure	4 bar - 6 bar ; 20 °C
Solubility	Water ; insoluble
Relative density	1.18 ; 20 °C ; Liquid
Absolute density	1180 kg/m ³ ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (aerosol)
	Not applicable (non-soluble in water)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. May build up electrostatic charges: risk of ignition. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

On burning: release of toxic and corrosive gases/vapours (hydrogen chloride, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

TRIMFIX WT

No (test)data on the mixture available

Judgement is based on the relevant ingredients

TRIMFIX WT

dichloromethane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 2000 mg/kg		Rat (male / female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg	24 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC50		49 mg/l air	7 h	Mouse	Experimental value	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 5840 mg/kg bw		Rat	Read-across	
Dermal	LD50		2800 mg/kg bw - 3100 mg/kg bw	24 h	Rat (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 21 mg/l	4 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC50		> 25.2 mg/l	4 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

TRIMFIX WT

No (test)data on the mixture available

Classification is based on the relevant ingredients

dichloromethane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating		10 minutes		Rabbit	Experimental value	Single treatment
Skin	Irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Irritating	OECD 404	4 h	1; 24; 48; 72 hrs; 7; 14 days	Rabbit	Experimental value	

Conclusion

Causes skin irritation.

Causes serious eye irritation.

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

TRIMFIX WT

No (test)data on the mixture available

Judgement is based on the relevant ingredients

dichloromethane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male / female)	Read-across	

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

TRIMFIX WT

No (test)data on the mixture available

Classification is based on the relevant ingredients

TRIMFIX WT

dichloromethane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 453	6 mg/kg bw/day	Blood; liver	No effect	104 weeks (daily)	Rat (male / female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	200 ppm	Liver	No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	
Inhalation		Human observation		Central nervous system	Central nervous system depression		Human	Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Dermal	NOAEL	Equivalent to OECD 453	0.5 ml			52 weeks (3 times / week) - 104 weeks (3 times / week)	Mouse (male / female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	24300 mg/m ³ air		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	
Inhalation			STOT SE cat.3					Literature study

Conclusion

May cause drowsiness or dizziness.
Not classified for subchronic toxicity

Mutagenicity (in vitro)

TRIMFIX WT

No (test)data on the mixture available
Judgement is based on the relevant ingredients
dichloromethane

Result	Method	Test substrate	Effect	Value determination	Remark
Positive with metabolic activation, positive without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)		Experimental value	
Positive with metabolic activation, positive without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	

Mutagenicity (in vivo)

TRIMFIX WT

No (test)data on the mixture available
Judgement is based on the relevant ingredients
dichloromethane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)		Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

TRIMFIX WT

No (test)data on the mixture available
Classification is based on the relevant ingredients
dichloromethane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	1000 ppm	102 weeks (6h / day, 5 days / week)	Rat (female)	Tumor formation	Mammary gland	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	2000 ppm	102 weeks (6h / day, 5 days / week)	Rat (male)	No carcinogenic effect		Experimental value

Conclusion

Suspected of causing cancer.

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

8 / 16

TRIMFIX WT

Reproductive toxicity

TRIMFIX WT

No (test) data on the mixture available

Judgement is based on the relevant ingredients
dichloromethane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1226 ppm	10 day(s)	Rat	Minor skeletal variations	Foetus	Experimental value
Maternal toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1226 ppm	10 day(s)	Rat	Methemoglobinemia	Blood	Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	≥ 1500 ppm	14 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	10560 mg/m ³ air	10 days (6h / day)	Mouse	No effect		Read-across
Maternal toxicity	NOAEL	Equivalent to OECD 414	3168 mg/m ³ air	10 days (6h / day)	Mouse (female)	No effect		Read-across
Effects on fertility	NOAEL	Equivalent to OECD 416	31680 mg/m ³ air	13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Read-across

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

TRIMFIX WT

No (test) data on the mixture available

Chronic effects from short and long-term exposure

TRIMFIX WT

Dry skin.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

TRIMFIX WT

No (test) data on the mixture available

Classification is based on the relevant ingredients
dichloromethane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		193 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	EPA 660/3 - 75/009	27 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50		> 660 mg/l	96 h	Selenastrum capricornutum			Literature study; Growth rate
Long-term toxicity fish	NOEC	ASTM E729-80	83 mg/l	28 day(s)	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Growth rate
Long-term toxicity aquatic crustacea	NOEC		6.2 mg/l - 13.3 mg/l	21 day(s)	Daphnia magna			QSAR
Toxicity aquatic micro-organisms	EC50		7 mg/l	48 h	Bacteria			Literature study; Methanogenesis
	EC50	OECD 209	2590 mg/l	40 minutes	Activated sludge	Static system	Fresh water	Experimental value

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

9 / 16

TRIMFIX WT

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	11.4 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	3 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	30 mg/l - 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR		2.045 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Toxicity aquatic micro-organisms	EL50		35.57 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Continuous exposure

Conclusion

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

dichloromethane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	68 %; GLP	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	79.306 day(s)	1.5E6 /cm ³	Calculated value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; Oxygen consumption	28 day(s)	Experimental value

Conclusion

Water

Does not contain any not readily biodegradable component(s)

12.3. Bioaccumulative potential

TRIMFIX WT

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

dichloromethane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	2 - 40; GLP	6 week(s)	Cyprinus carpio	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 107		1.25	20 °C	Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

dichloromethane

(log) Koc

Parameter	Method	Value	Value determination
log Koc		1.67	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

TRIMFIX WT

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

10 / 16

TRIMFIX WT

Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)
None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

dichloromethane

Greenhouse gases

Included in the list of substances which may contribute to the greenhouse effect (IPCC)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Remove waste in accordance with local and/or national regulations. Do not discharge into surface water (Directive 2000/60/EC, Council Decision 2455/2001/EC). Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

14.4. Packing group

Packing group	
---------------	--

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

11 / 16

TRIMFIX WT

Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

12 / 16

TRIMFIX WT

Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
660 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC, 2004/37/EC and amendments)

dichloromethane

Product name	Skin resorption
Methylene chloride; Dichloromethane	Skin

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· dichloromethane · hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

13 / 16

TRIMFIX WT

		referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
dichloromethane	Dichloromethane	<p>1. Paint strippers containing dichloromethane in a concentration equal to or greater than 0,1 % by weight shall not be:</p> <p>a) placed on the market for the first time for supply to the general public or to professionals after 6 December 2010;</p> <p>b) placed on the market for supply to the general public or to professionals after 6 December 2011;</p> <p>c) used by professionals after 6 June 2012. For the purposes of this entry:</p> <p>i) "professional" means any natural or legal person, including workers and self-employed workers undertaking paint stripping in the course of their professional activity outside an industrial installation;</p> <p>ii) "industrial installation" means a facility used for paint stripping activities.</p> <p>2. By way of derogation from paragraph 1, Member States may allow on their territories and for certain activities the use, by specifically trained professionals, of paint strippers containing dichloromethane and may allow the placing on the market of such paint strippers for supply to those professionals. Member States making use of this derogation shall define appropriate provisions for the protection of the health and safety of those professionals using paint strippers containing dichloromethane and shall inform the Commission thereof. Those provisions shall include a requirement that a professional shall hold a certificate that is accepted by the Member State in which that professional operates, or provide other documentary evidence to that effect, or be otherwise approved by that Member State, so as to demonstrate proper training and competence to safely use paint strippers containing dichloromethane. The Commission shall prepare a list of the Member States which have made use of the derogation in this paragraph and make it publicly available over the Internet.</p> <p>3. A professional benefiting from the derogation referred to in paragraph 2 shall operate only in Member States which have made use of that derogation. The training referred to in paragraph 2 shall cover as a minimum:</p> <p>(a) awareness, evaluation and management of risks to health, including information on existing substitutes or processes, which under their conditions of use are less hazardous to the health and safety of workers;</p> <p>(b) use of adequate ventilation;</p> <p>(c) use of appropriate personal protective equipment that complies with Directive 89/686/EEC. Employers and self-employed workers shall preferably replace dichloromethane with a chemical agent or process which, under its conditions of use, presents no risk, or a lower risk, to the health and safety of workers. Professional shall apply all relevant safety measures in practice, including the use of personal protective equipment.</p> <p>4. Without prejudice to other Community legislation on workers protection, paint strippers containing dichloromethane in concentrations equal to or greater than 0,1 % by weight may be used in industrial installations only if the following minimum conditions are met:</p> <p>(a) effective ventilation in all processing areas, in particular for the wet processing and the drying of stripped articles: local exhaust ventilation at strip tanks supplemented by forced ventilation in those areas, so as to minimise exposure and to ensure compliance, where technically feasible, with relevant occupational exposure limits;</p> <p>(b) measures to minimise evaporation from strip tanks comprising: lids for covering strip tanks except during loading and unloading; suitable loading and unloading arrangements for strip tanks; and wash tanks with water or brine to remove excess solvent after unloading;</p> <p>(c) measures for the safe handling of dichloromethane in strip tanks comprising: pumps and pipework for transferring paint stripper to and from strip tanks; and suitable arrangements for safe cleaning of tanks and removal of sludge;</p> <p>(d) personal protective equipment that complies with Directive 89/686/EEC comprising: suitable protective gloves, safety goggles and protective clothing; and appropriate respiratory protective equipment where compliance with relevant occupational exposure limits cannot be otherwise achieved;</p> <p>(e) adequate information, instruction and training for operators in the use of such equipment.</p> <p>5. Without prejudice to other Community provisions concerning the classification, labelling and packaging of substances and mixtures, by 6 December 2011 paint strippers containing dichloromethane in a concentration equal to or greater than 0,1 % by weight shall be visibly, legibly and indelibly marked as follows: "Restricted to industrial use and to professionals approved in certain EU Member States — verify where use is allowed."</p>

National legislation Belgium

TRIMFIX WT

No data available

dichloromethane

Résorption peau	Chlorure de méthylène; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

petroleum gases, liquefied

Additional classification	Pétrole (gaz liquéfié); C; La mention "C" signifie que l'agent en question relève du champ d'application de l'arrêté royal du 2 décembre 1993 concernant la protection des travailleurs contre les risques liés à l'exposition à des agents cancérigènes et mutagènes et reprotoxiques au travail.
---------------------------	--

National legislation The Netherlands

TRIMFIX WT

Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

14 / 16

TRIMFIX WT

dichloromethane

Huidopname (wettelijk)	Methyleenchloride/ dichloormethaan; H
------------------------	---------------------------------------

National legislation France

TRIMFIX WT

No data available

dichloromethane

Catégorie cancérogène	Dichlorométhane; C2
Risque de pénétration percutanée	Dichlorométhane; Risque de pénétration percutanée

National legislation Germany

TRIMFIX WT

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

dichloromethane

TA-Luft	5.2.5/1
TRGS900 - Risiko der Fruchtschädigung	Dichlormethan; Z; Risiko der Fruchtschädigung kann auch bei Einhaltung des AGW und des BGW nicht ausgeschlossen werden.
Hautresorptive Stoffe	Dichlormethan; H; Hautresorptiv

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

TA-Luft	5.2.5
---------	-------

National legislation Austria

TRIMFIX WT

No data available

dichloromethane

Krebserzeugend	Dichlormethan (R 30); III B
besondere Gefahr der Hautresorption	Dichlormethan (R 30); H

National legislation United Kingdom

TRIMFIX WT

No data available

dichloromethane

Skin absorption	Dichloromethane; Sk
-----------------	---------------------

Other relevant data

TRIMFIX WT

No data available

dichloromethane

IARC - classification	2A; Dichloromethane
TLV - Carcinogen	Dichloromethane; A3

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

dichloromethane

A chemical safety assessment has been performed.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
Erc50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

15 / 16

TRIMFIX WT

LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3, 9, 12, 15

Publication date: 2005-12-01

Date of revision: 2022-01-31

Revision number: 0500

BIG number: 42911

16 / 16