SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



XPR-90

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: XPR-90Registration number REACH: Not appProduct type REACH: Mixture

: Not applicable (mixture) : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio* Industrielaan 5B B-2250 Olen ☎ +32 14 25 76 40 ➡ +32 14 22 02 66 info@novatio.be *NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V. Industrielaan 5B B-2250 Olen ☎ +32 14 85 97 37 ➡ +32 14 85 97 38 info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) : +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	zard statements			
Aerosol category 1 H222: Extremely flammable aerosol.					
Aerosol	category 1	H229: Pressurised container: May burst if heated.			
STOT SE	category 3	H336: May cause drowsiness or dizziness.			
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.			

2.2. Label elements



H336	May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effect	S.
P-statements		
P210	Keep away from heat, hot surfaces, sparks, op	en flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignitic	on source.
P251	Do not pierce or burn, even after use.	
P261	Avoid breathing spray.	
ed by: Brandweerinformat	tiecentrum voor gevaarlijke stoffen vzw (BIG)	Publication date: 2010-07-09

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG) Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be © BIG vzw Reason for revision: 3, 8, 15

Revision number: 0501

Date of revision: 2022-01-30

16239-032-en

878-2

P304 + P340 P410 + P412

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

Supplemental information FUH066

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119471843-32	927-241-2	C≤80%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412 EUH066	(1)(10)	UVCB	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
butane 01-2119474691-32	106-97-8 203-448-7	C≤9%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(21) 1,3-butadiene < 0.1%

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eve contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms After inhalation: Dizziness. Drowsiness. After skin contact: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Cracking of the skin. After eve contact: No effects known. After ingestion: No effects known. 4.2.2 Delayed symptoms No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 3, 8, 15

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher. Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight. Protect against frost.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol

7.2.4 Non suitable packaging material: No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values If limit values are applicable and available these will be listed below.

Belgium

Reason for revision: 3, 8, 15

Publication date: 2010-07-09 Date of revision: 2022-01-30

BIG number: 49027

		XPR-90		
Butane, tous isomères: n-b	utane	Short time value		980 ppm
		Short time value		2370 mg/m
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)		Time-weighted average	e exposure limit 8 h	1000 ppm
France				
n-Butane		Time-weighted average réglementaire indicativ	e exposure limit 8 h (VL: Valeur non /e)	800 ppm
		Time-weighted average réglementaire indicativ	e exposure limit 8 h (VL: Valeur non /e)	1900 mg/n
Gormany			-,	1
Germany Butan		Time-weighted average	e exposure limit 8 h (TRGS 900)	1000 ppm
			e exposure limit 8 h (TRGS 900)	2400 mg/n
Propan			e exposure limit 8 h (TRGS 900)	1000 ppm
•			e exposure limit 8 h (TRGS 900)	1800 mg/n
Austria				
Butan (beide Isomeren): n-E 600a)	Butan (R 600) Isobutan (R	Tagesmittelwert (MAK))	800 ppm
,		Tagesmittelwert (MAK))	1900 mg/n
		Kurzzeitwert 60(Mow)	3х (МАК)	1600 ppm
		Kurzzeitwert 60(Mow)	Зх (МАК)	3800 mg/m
Propan (R 290)		Tagesmittolwort (NAAK)	1	1000 ppm
		Tagesmittelwert (MAK) Tagesmittelwert (MAK)		1800 ppm 1800 mg/n
		Kurzzeitwert 60(Mow)	-	2000 ppm
		Kurzzeitwert 60(Mow)		3600 mg/n
				5000 mg/m
UK Butane		Time weighted average	o overegung limit Q h (Merturlage overegung	limit COO ana
Butane		(EH40/2005))	e exposure limit 8 h (Workplace exposure	
		Time-weighted average (EH40/2005))	limit 1450 mg/n	
		Short time value (Work	xplace exposure limit (EH40/2005))	750 ppm
		Short time value (Work	place exposure limit (EH40/2005))	1810 mg/n
USA (TLV-ACGIH)				
Dutono in		Short time value (TLV -	Adapted Value)	
Butane, isomers b) National biological limit val If limit values are applicable ar 2 Sampling methods				1000 ppm
b) National biological limit val	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will	d below. ure as intended be listed below.		1000 ppm
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will <u>tes, isoalkanes, cyclics, < 2% a</u>	d below. ure as intended be listed below.	Value Ren	
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkan	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will	d below. cure as intended be listed below. romatics		
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkan Effect level (DNEL/DMEL) DNEL	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will <u>tes, isoalkanes, cyclics, < 2% an</u> Type Long-term systemic e Long-term systemic e	d below. ure as intended be listed below. <u>romatics</u> ffects inhalation	Value Ren	
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkan Effect level (DNEL/DMEL)	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% and Type Long-term systemic e Long-term systemic e tion	d below. ure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u>	Value Ren 871 mg/m ³	
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when I limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkan Effect level (DNEL/DMEL) DNEL DNEL	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% and Type Long-term systemic e Long-term systemic e tion	d below. ure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u>	Value Ren 871 mg/m ³	nark
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it wi 3 Applicable limit values whee If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkan Effect level (DNEL/DMEL) DNEL DNEL DNEL-	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will <u>tes, isoalkanes, cyclics, < 2% and</u> <u>Type</u> Long-term systemic e Long-term systemic e tion tes, isoalkanes, cyclics, < 2% and tes, isoalkanes, cyclics, < 2% a	d below. cure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>romatics</u>	Value Rem 871 mg/m³ 77 mg/kg bw/day	nark
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it wi 3 Applicable limit values whee If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General populat hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL)	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% ar Long-term systemic e tion tes, isoalkanes, cyclics, < 2% ar Type Long-term systemic e Long-term systemic e Long-term systemic e	d below. ure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects inhalation</u> <u>ffects dermal</u>	Value Ren 871 mg/m³ 77 mg/kg bw/day Value Ren 185 mg/m³ 46 mg/kg bw/day	nark
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it wi 3 Applicable limit values whee If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General populat hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL)	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% an Type Long-term systemic e Long-term systemic e tion tes, isoalkanes, cyclics, < 2% an Type Long-term systemic e Long-term systemic e	d below. ure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects inhalation</u> <u>ffects dermal</u>	Value Ren 871 mg/m³ 77 mg/kg bw/day 77 mg/kg bw/day 185 mg/m³	nark
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General popular hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL 5 Control banding If applicable and available is xposure controls information in this section evant exposure scenarios th 1 Appropriate engineering coi	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% ar Long-term systemic e Long-term systemic e tion tes, isoalkanes, cyclics, < 2% ar Type Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e long-term systemic e ti will be listed below. is a general description. If iat correspond to your ider ntrols appliances and lighting syst urces/sparks. Measure the ures, such as personal protect	d below. cure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects oral</u> <u>applicable and available</u> <u>itified use.</u> tem. Take precautions ag concentration in the air ive equipment	Value Ren 871 mg/m³ 77 mg/kg bw/day 77 mg/kg bw/day 86 mg/kg bw/day 46 mg/kg bw/day 46 mg/kg bw/day 46 mg/kg bw/day 90 mg/kg bw/day 2, exposure scenarios are attached in gainst electrostatic charges. Keep awa	nark
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values when If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General popular hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL 5 Control banding If applicable and available is exposure controls information in this section evant exposure scenarios th 1 Appropriate engineering co Use spark-/explosionproof a Keep away from ignition so 2 Individual protection measu	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% ar Long-term systemic e Long-term systemic e tion tes, isoalkanes, cyclics, < 2% ar Type Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e long-term systemic e ti will be listed below. is a general description. If iat correspond to your ider ntrols appliances and lighting syst urces/sparks. Measure the ures, such as personal protect	d below. cure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects oral</u> <u>applicable and available</u> <u>itified use.</u> tem. Take precautions ag concentration in the air ive equipment	Value Ren 871 mg/m³ 77 mg/kg bw/day 77 mg/kg bw/day 86 mg/kg bw/day 46 mg/kg bw/day 46 mg/kg bw/day 46 mg/kg bw/day 90 mg/kg bw/day 2, exposure scenarios are attached in gainst electrostatic charges. Keep awa	nark nark annex. Always us
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it wi 3 Applicable limit values when If limit values are applicable 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General popular hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL 5 Control banding If applicable and available is xposure controls information in this section evant exposure scenarios th 1 Appropriate engineering con Use spark-/explosionproof a Keep away from ignition so 2 Individual protection measu Observe normal hygiene sta	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% ar Long-term systemic e Long-term systemic e tion tes, isoalkanes, cyclics, < 2% ar Type Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e long-term systemic e ti will be listed below. is a general description. If iat correspond to your ider ntrols appliances and lighting syst urces/sparks. Measure the ures, such as personal protect	d below. cure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects oral</u> <u>applicable and available</u> <u>itified use.</u> tem. Take precautions ag concentration in the air ive equipment	Value Ren 871 mg/m³ 77 mg/kg bw/day 77 mg/kg bw/day 185 mg/m³ 46 mg/kg bw/day 46 mg/kg bw/day 46 mg/kg bw/day 185 mg/m³ 46 mg/kg bw/day 190 mg/kg bw/day 87 mg/kg bw/day 100 mg/kg bw/day 9 mg/kg bw/day 100 mg/kg bw/day 10 mg/kg bw/day 100 mg/kg bw/kg bw	nark
b) National biological limit val If limit values are applicable ar 2 Sampling methods If applicable and available it wi 3 Applicable limit values when If ilmit values are applicable 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General popular hydrocarbons, C9-C10, n-alkar Effect level (DNEL/DMEL) DNEL DNEL 5 Control banding If applicable and available is exposure controls information in this section evant exposure scenarios th 1 Appropriate engineering con Use spark-/explosionproof a Keep away from ignition so 2 Individual protection measu Observe normal hygiene sta espiratory protection:	nd available these will be lister ill be listed below. n using the substance or mixt e and available these will tes, isoalkanes, cyclics, < 2% ar Long-term systemic e Long-term systemic e tion tes, isoalkanes, cyclics, < 2% ar Type Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e Long-term systemic e long-term systemic e ti will be listed below. is a general description. If iat correspond to your ider ntrols appliances and lighting syst urces/sparks. Measure the ures, such as personal protect	d below. cure as intended be listed below. <u>romatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects oral</u> <u>applicable and available</u> <u>itified use.</u> tem. Take precautions ag concentration in the air ive equipment	Value Ren 871 mg/m³ 77 mg/kg bw/day 77 mg/kg bw/day 185 mg/m³ 46 mg/kg bw/day 46 mg/kg bw/day 46 mg/kg bw/day 190 mg/kg bw/day 2, exposure scenarios are attached in gainst electrostatic charges. Keep awa regularly. 100 mg/kg bw/day	nark

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol				
Odour	Characteristic odour				
Odour threshold	No data available in the literature				
Colour	No data available on colour				
Particle size	Not applicable (mixture)				
Explosion limits	0.6 - 9.5 vol % ; Propellant				
Flammability	Extremely flammable aerosol.				
Log Kow	Not applicable (mixture)				
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid				
Kinematic viscosity	1 mm²/s ; 40 °C ; Liquid				
Melting point	Not applicable (aerosol)				
Boiling point	-42 °C - 166 °C ; Liquid				
Relative vapour density	>1				
Vapour pressure	8530 hPa ; 20 °C				
Solubility	Water ; insoluble				
Relative density	0.76 ; 20 °C ; Liquid				
Absolute density	64 kg/m³ ; 20 °C				
Decomposition temperature	No data available in the literature				
Auto-ignition temperature	Not applicable (aerosol)				
Flash point	Not applicable (aerosol)				
рН	Not applicable (aerosol)				

9.2. Other information

Evaporation rate

0.35 ; Butyl acetate ; Liquid

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Unstable on exposure to heat.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

<u>XPR-90</u>

No (test)data on the mixture available

Reason for revision: 3, 8, 15

Judgement is based on the relevant ingredients hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg bw		Rat (male /	Read-across	
		401			female)		
Dermal	LD50	Equivalent to OECD	> 3160 mg/kg bw	24 h	Rabbit (male /	Experimental value	
		402			female)		
Inhalation (aerosol)	LC50	Equivalent to OECD	> 5.6 mg/l air	4 h	Rat (male /	Experimental value	
		403	-		female)		

Conclusion

Not classified for acute toxicity

Corrosion/irritation

<u>XPR-90</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Rout	te of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye		0	Equivalent to OECD 405		1; 24; 48; 72; 168 hours			Single treatment
Skin	I		Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

Conclusion

Not classified as irritating to the respiratory system Not classified as irritating to the skin

Not classified as irritating to the eyes

Respiratory or skin sensitisation

<u>XPR-90</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Route of exposure	Result	Method	••••••	Observation time	Species	Value determination	Remark
ĺ	Skin	0	Equivalent to OECD 406		24; 48 hours	Guinea pig (female)	Read-across	

Conclusion

Not classified as sensitizing for skin

Specific target organ toxicity

<u>XPR-90</u>

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	> 1000 mg/kg bw/day		No effect		Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400 mg/m ³ air		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation			STOT SE cat.3		Drowsiness, dizziness			Literature study

Conclusion

May cause drowsiness or dizziness. Not classified for subchronic toxicity

Mutagenicity (in vitro)

<u>XPR-90</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

Reason for revision: 3, 8, 15

Publication date: 2010-07-09 Date of revision: 2022-01-30

BIG number: 49027

Mutagenicity (in vivo)

<u>XPR-90</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD	5 days (6h / day)	Rat (male / female)		Read-across
	478				

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

<u>XPR-90</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation	NOAEC	Equivalent to OECD 453		105 weeks (6h / day, 5 days / week)	Rat (female)	No carcinogenic effect		Read-across
(vapours)		0ECD 453	mg/m² air	5 days / week)		enect		

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

<u>XPR-90</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	≥ 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	> 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Read-across
Effects on fertility	NOAEL	Equivalent to OECD 413	> 1000 mg/kg bw/day	14 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Read-across

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

<u>XPR-90</u>

Classification is based on the relevant ingredients hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
Skin					Skin dryness or cracking		Literature study

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

<u>XPR-90</u>

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

<u>XPR-90</u>

No (test)data on the mixture available Classification is based on the relevant ingredients

Reason for revision: 3, 8, 15

Publication date: 2010-07-09 Date of revision: 2022-01-30

Revision number: 0501

drocarbons, C9-C10, n-alkane/	irocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics							
	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	10 mg/l - 30 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	22 mg/l - 46 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOEL	OECD 201	< 1 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEL		0.182 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		0.317 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Nominal concentration

Conclusion

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	89 %	28 day(s)	Experimental value
Phototransformation air (DT50 air)			
Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	18.679 h	1.5E6 /cm ³	Calculated value

Conclusion

Water Does not contain any not readily biodegradable component(s)

12.3. Bioaccumulative potential

<u>XPR-90</u>

Log	Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	551.7 l/kg; Fresh weight			Estimated value
og Kow		·			·
Method	Rema	rk	Value	Temperature	Value determination
			4.66		Experimental value

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

(log) Koc

Parameter		Method		N	/alue	Value determina	ation
log Koc		SRC PCKC	CWIN v2.0	2	2.380	Calculated value	
Percent distribution	_						

Method	Fraction air	 Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	34.9 %	0.553 %	1.19 %	63.4 %	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

<u>XPR-90</u>

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Reason for revision: 3, 8, 15

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14. <u>1. UN number</u>	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14. <u>1</u> . UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

Reason for revision: 3, 8, 15

14. <u>1</u> . UN number				
UN number	1950			
14.2. UN proper shipping name				
Proper shipping name	aerosols			
14.3. Transport hazard class(es)				
Class	2			
Classification code	5F			
14.4. Packing group				
Packing group				
Labels	2.1			
14.5. Environmental hazards				
Environmentally hazardous substance mark	no			
14.6. Special precautions for user				
Special provisions	190			
Special provisions	327			
Special provisions	344			
Special provisions	625			
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for			
	liquids. A package shall not weigh more than 30 kg. (gross mass)			

Sea (IMDG/IMSBC)

14.1. UN number					
UN number	1950				
14.2. UN proper shipping name					
Proper shipping name	aerosols				
14.3. Transport hazard class(es)					
Class	2.1				
14.4. Packing group					
Packing group					
Labels	2.1				
14.5. Environmental hazards					
Marine pollutant	-				
Environmentally hazardous substance mark	no				
14.6. Special precautions for user					
Special provisions	190				
Special provisions	277				
Special provisions	327				
Special provisions	344				
Special provisions	381				
Special provisions	63				
Special provisions	959				
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)				
14.7. Maritime transport in bulk according to IMO instruments					
Annex II of MARPOL 73/78	Not applicable				

Air (ICAO-TI/IATA-DGR)

14. <u>1. UN number</u>	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

		-90			
TION 15: Regulatory	information				
	onmental regulations/legislation sp	ecific for th	e substance o	r mixture	
European legislation:	,0				
VOC content Directive 2010/75	5/EU				
VOC content		Remark			
100.000 %					
709.999 g/l					
Directive 2012/18/EU (Seveso					
Threshold values under no Substance or category	rmal circumstances	Low tier	Top tier	Group	For this substance or mixtur
Substance of category		(tonnes)	(tonnes)	Gloup	the summation rule has to be applied for:
P3b FLAMMABLE AEROSOL	S	5000 (net)	50000 (net)	None	Flammability
≥30% aliphatic hydrocarbon REACH Annex XVII - Restriction Contains component(s) sub		on (EC) No 1907	7/2006: restrictio	ns on the manu	ufacture, placing on the market
j.	Designation of the substance, of the group of	Conditions of re	estriction		
· hydrocarbons, C9-C10, n-alkanes,	substances or of the mixture Liquid substances or mixtures fulfilling the	1. Shall not be u	used in:		
isoalkanes, cyclics, < 2% aromatics	criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	 ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even with ornamental aspects, Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: can be used as fuel in decorative oil lamps for supply to the general public, and, present an aspiration hazard and are labelled with H304, Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legible and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are legible and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labe			
isoalkanes, cyclics, < 2% aromatics	category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	dispensers are i purposes such a — metallic glitt — artificial snov — "whoopee" o — silly string ae — imitation exx — horns for pai — decorative fl — artificial cob — stink bombs. 2. Without prej packaging and I market that the and indelibly w "For profession 3. By way of de referred to Arti 4. The aerosol of	intended for supply as the following: er intended mainly w and frost, cushions, crosols, crement, rties, akes and foams, webs, udice to the applica abelling of substan p packaging of aero: ith: al users only". rogation, paragrapi cle 8 (1a) of Counci	to the general put for decoration, tion of other Cor ces, suppliers sha sol dispensers ref is 1 and 2 shall no Directive 75/ 32 to in paragraphs	nmunity provisions on the classification Il ensure before the placing on the erred to above is marked visibly, legit ot apply to the aerosol dispensers 4/EEC. 1 and 2 shall not be placed on the
National legislation Belgium					
<u>XPR-90</u>					
No data available					
National legislation The Netherl	ands				
son for revision: 3, 8, 15			Publication	n date: 2010-07	7-09
			Date of re	vision: 2022-01	-30
ision number: 0501			BIG numb	er: 49027	11

<u>XPR-90</u>

Waterbezwaarlijkheid

Z (2); Algemene Beoordelingsmethodiek (ABM)

National legislation France

<u>XPR-90</u> No data available

National legislation Germany

<u>~</u>				
	Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge		
	WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017		
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	TA-Luft	5.2.5/I		

National legislation Austria

<u>XPR-90</u>

No data available

National legislation United Kingdom XPR-90

No data available

Other relevant data

<u>XPR-90</u>

No data available

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

INTERNAL CLASSIFICATION BY BIG (*) ADI Acceptable daily intake AOEL Acceptable operator exposure level ATE Acute Toxicity Estimate CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe) DMEL Derived Minimal Effect Level DNEL Derived No Effect Level FC50 Effect Concentration 50 % ErC50 EC50 in terms of reduction of growth rate LC50 Lethal Concentration 50 % LD50 Lethal Dose 50 % NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration Organisation for Economic Co-operation and Development OECD PBT Persistent, Bioaccumulative & Toxic PNEC Predicted No Effect Concentration STP Sludge Treatment Process vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3, 8, 15

Publication date: 2010-07-09 Date of revision: 2022-01-30

BIG number: 49027