

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

NAE-1600 B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : NAE-1600 B
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Adhesive

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)
Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2166 (Public 8 am- 10 pm)
Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2566 (Professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Acute Tox.	category 4	H312: Harmful in contact with skin.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if swallowed.
Skin Corr.	category 1B	H314: Causes severe skin burns and eye damage.
Eye Dam.	category 1	H318: Causes serious eye damage.
STOT SE	category 3	H335: May cause respiratory irritation.

2.2. Label elements



Contains: p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄); N,N'-bis(3-aminopropyl)ethylenediamine; 3,3'-oxybis(ethyleneoxy)bis(propylamine).

Signal word Danger

H-statements

H317 May cause an allergic skin reaction.
H312 Harmful in contact with skin.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

NAE-1600 B

P-statements

P280	Wear protective gloves, protective clothing and eye protection/face protection.
P260	Do not breathe dust.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
p-toluenesulphonic acid (containing a maximum of 5 % H2SO4) 01-2119538811-39	104-15-4 203-180-0	C<30%	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT SE 3; H335: C≥20%, (CLP Annex VI (ATP 0))	(1)(10)	Constituent	
N,N'-bis(3-aminopropyl)ethylenediamine 01-2119976331-37	10563-26-5 234-147-9	C<30%	Acute Tox. 3; H311 Skin Sens. 1A; H317 Acute Tox. 4; H302 STOT RE 2; H373 Skin Corr. 1B; H314 Eye Dam. 1; H318	(1)(10)	Constituent	
3,3'-oxybis(ethyleneoxy)bis(propylamine) 01-2119963377-26	4246-51-9 224-207-2	C<30%	Skin Sens. 1; H317 Skin Corr. 1B; H314 Eye Dam. 1; H318	(1)(10)	Constituent	
calcium carbonate	471-34-1 207-439-9	C<45%		(2)	Constituent	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. Immediately consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately for 30 minutes with (lukewarm) water. Cut clothing; never remove burnt clothing from the wound. Do not give any pain medication. Consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a doctor/medical service.

After ingestion:

Rinse mouth with water. Immediately consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Irritation of the respiratory tract. Irritation of the nasal mucous membranes. EXPOSURE TO HIGH CONCENTRATIONS: Corrosion of the upper respiratory tract.

After skin contact:

Caustic burns/corrosion of the skin.

After eye contact:

Corrosion of the eye tissue.

After ingestion:

Burns to the gastric/intestinal mucosa. Possible esophageal perforation.

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

2 / 18

NAE-1600 B

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (not alcohol-resistant).

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, sulphur oxides, carbon monoxide - carbon dioxide).

5.3. Advice for firefighters

5.3.1 Instructions:

Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water. Use water moderately and if possible collect or contain it. Take account of toxic fire-fighting water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Face shield (EN 166). Corrosion-proof suit (EN 14605). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames. Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Face shield (EN 166). Corrosion-proof suit (EN 14605).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the solid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Solid spill: cover with absorbent material. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately. Keep container tightly closed. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Meet the legal requirements.

7.2.2 Keep away from:

Heat sources.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

NAE-1600 B

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Calcium (carbonate de)	Time-weighted average exposure limit 8 h	10 mg/m ³
------------------------	--	----------------------

France

Calcium (carbonate de)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m ³
------------------------	--	----------------------

UK

Calcium carbonate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	10 mg/m ³ (1)
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	4 mg/m ³ (2)

(1) Inhalable dust

(2) Respirable dust

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
Calciumdicarbonate	NIOSH	7020
p-Toluenesulfonic acid	NIOSH	5043

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	24.7 mg/m ³	
	Long-term systemic effects dermal	7 mg/kg bw/day	

N,N'-bis(3-aminopropyl)ethylenediamine

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1.5 mg/m ³	
	Long-term systemic effects dermal	0.42 mg/kg bw/day	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m ³	
	Acute systemic effects inhalation	178 mg/m ³	
	Long-term systemic effects dermal	8 mg/kg bw/day	

calcium carbonate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	6.36 mg/m ³	

DNEL/DMEL - General population

p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	4.35 mg/m ³	
	Long-term systemic effects dermal	2.5 mg/kg bw/day	
	Long-term systemic effects oral	2.5 mg/kg bw/day	

N,N'-bis(3-aminopropyl)ethylenediamine

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	0.26 mg/m ³	
	Long-term systemic effects dermal	0.15 mg/kg bw/day	
	Long-term systemic effects oral	0.15 mg/kg bw/day	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	10 mg/m ³	
	Acute systemic effects inhalation	31 mg/m ³	
	Long-term systemic effects dermal	3 mg/kg bw/day	
	Long-term systemic effects oral	3 mg/kg bw/day	

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

4 / 18

NAE-1600 B

calcium carbonate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	1.06 mg/m ³	
	Long-term systemic effects oral	6.1 mg/kg bw/day	
	Acute systemic effects oral	6.1 mg/kg bw/day	

PNEC

p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Compartments	Value	Remark
Fresh water	0.073 mg/l	
Marine water	0.007 mg/l	
Fresh water (intermittent releases)	0.73 mg/l	
STP	65 mg/l	
Fresh water sediment	0.35 mg/kg sediment dw	
Marine water sediment	0.035 mg/kg sediment dw	
Soil	0.028 mg/kg soil dw	

N,N'-bis(3-aminopropyl)ethylenediamine

Compartments	Value	Remark
Fresh water	0.144 mg/l	
Fresh water (intermittent releases)	0.43 mg/l	
Marine water	0.014 mg/l	
STP	3.4 mg/l	
Fresh water sediment	45.3 mg/kg sediment dw	
Marine water sediment	4.53 mg/kg sediment dw	
Soil	8.96 mg/kg soil dw	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Compartments	Value	Remark
Fresh water	0.492 mg/l	
Marine water	0.049 mg/l	
Fresh water (intermittent releases)	2.2 mg/l	
STP	500 mg/l	
Fresh water sediment	2.45 mg/kg sediment dw	
Marine water sediment	0.245 mg/kg sediment dw	
Soil	0.202 mg/kg soil dw	

calcium carbonate

Compartments	Value	Remark
STP	100 mg/l	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

High gas/vapour concentration: full face mask with filter type B.

b) Hand protection:

Protective gloves against chemicals (EN 374).

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Corrosion-proof clothing (EN 14605).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Paste
Colour	White
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	No data available (test not performed)
Boiling point	No data available (test not performed)
Flammability	Not classified as flammable
Explosion limits	No data available (test not performed)
Flash point	No data available (test not performed)

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

5 / 18

NAE-1600 B

Auto-ignition temperature	No data available (test not performed)
Decomposition temperature	No data available (test not performed)
pH	Not applicable (non-soluble in water)
Kinematic viscosity	No data available (test not performed)
Dynamic viscosity	No data available (test not performed)
Solubility	Water ; insoluble
Log Kow	Not applicable (mixture)
Vapour pressure	No data available (test not performed)
Absolute density	1450 kg/m ³ ; 20 °C
Relative density	1.45 ; 20 °C
Relative vapour density	No data available (test not performed)
Particle size	No data available (test not performed)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating increases the fire hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, sulphur oxides, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

NAE-1600 B

No (test)data on the mixture available

Classification is based on the relevant ingredients

p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	1410 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50		50 mg/l - 100 mg/l	8 h	Rat (male / female)	Read-across	

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

N,N'-bis(3-aminopropyl)ethylenediamine

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	BASF test	1140 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	OECD 402	> 200 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	3160 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2150 mg/kg	24 h	Rat (male / female)	Experimental value	

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

6 / 18

NAE-1600 B

calcium carbonate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 420	> 2000 mg/kg		Rat (female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (aerosol)	LC50	OECD 403	> 3 mg/l air	4 h	Rat (male / female)	Experimental value	

Conclusion

Harmful in contact with skin.
Not classified as acute toxic if inhaled
Not classified as acute toxic if swallowed

Corrosion/irritation

NAE-1600 B

No (test)data on the mixture available
Classification is based on the relevant ingredients
p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage		5 seconds - 30 seconds		Rabbit	Read-across	Single treatment
Eye	Irritating; category 2					Annex VI	
Skin	Corrosive	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating; category 2					Annex VI	
Inhalation	Irritating; STOT SE cat.3					Annex VI	

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

N,N'-bis(3-aminopropyl)ethylenediamine

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Corrosive	Equivalent to OECD 404	20 h	24; 48; 72 hours	Rabbit	Experimental value	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage; category 1					Data waiving	
Skin	Corrosive	BASF test	1 h	24; 48; 72 hours	Rabbit	Experimental value	

Data waiving for eye corrosion based on corrosive properties

calcium carbonate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
In vitro	Not irritating	OECD 439	15 minutes		Reconstructed human epidermis	Experimental value	

Conclusion

Causes severe skin burns and eye damage.
May cause respiratory irritation.

Respiratory or skin sensitisation

NAE-1600 B

No (test)data on the mixture available
Classification is based on the relevant ingredients
p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	EU Method B.6			Guinea pig (female)	Experimental value	

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

7 / 18

NAE-1600 B

N,N'-bis(3-aminopropyl)ethylenediamine

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing	OECD 406			Guinea pig (female)	Experimental value	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing					QSAR	

calcium carbonate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value	

Conclusion

May cause an allergic skin reaction.
Not classified as sensitizing for inhalation

Specific target organ toxicity

NAE-1600 B

No (test) data on the mixture available
Classification is based on the relevant ingredients
p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 407	≥ 500 mg/kg bw/day	No effect	4 weeks (daily)	Rat (male / female)	Experimental value	
Dermal	NOAEL	EPA OPP 82-2	> 800 mg/kg bw/day	No effect	2 weeks (5 days / week)	Rat (male)	Read-across	

N,N'-bis(3-aminopropyl)ethylenediamine

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 422	30 mg/kg bw/day	No effect	29 day(s) - 53 day (s)	Rat (male / female)	Experimental value	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL systemic effects	OECD 422	≥ 600 mg/kg bw/day	No effect	59 day(s) - 62 day (s)	Rat (male / female)	Experimental value	

calcium carbonate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 422	1000 mg/kg bw/day	No effect	48 day(s)	Rat (male / female)	Experimental value	
Inhalation (dust)	NOAEC local effects	OECD 413	≥ 0.212 mg/m ³ air	No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (dust)	NOEC	OECD 413	0.399 mg/l	No adverse systemic effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

Conclusion

May cause damage to organs through prolonged or repeated exposure if swallowed.
Not classified as sub-chronically toxic in contact with skin
Not classified as sub-chronically toxic if inhaled

Mutagenicity (in vitro)

NAE-1600 B

No (test) data on the mixture available
Judgement is based on the relevant ingredients
p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster lung fibroblasts (V79)	No effect	Experimental value	

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

8 / 18

NAE-1600 B

N,N'-bis(3-aminopropyl)ethylenediamine

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

calcium carbonate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 473	Human lymphocytes	No effect	Experimental value	

Mutagenicity (in vivo)

NAE-1600 B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)	No effect	Read-across	Single treatment

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

NAE-1600 B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal	NOAEL	Equivalent to OECD 453	≥ 240 mg/kg bw/day	No carcinogenic effect	104 weeks (5 days / week)	Rat (male / female)	Read-across	

calcium carbonate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Unknown							Data waiving	

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

NAE-1600 B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	> 1000 mg/kg bw/day	10 day(s)	Rat	Foetus (no effect)	Read-across	
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	> 1000 mg/kg bw/day	10 day(s)	Rat	No effect	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 421	300 mg/kg bw/day	46 day(s)	Rat (male / female)	No effect	Read-across	

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

9 / 18

NAE-1600 B

N,N'-bis(3-aminopropyl)ethylenediamine

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	≥ 300 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	150 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 422	100 mg/kg bw/day	29 day(s) - 53 day (s)	Rat (male / female)	No effect	Experimental value	

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	≥ 600 mg/kg bw/day	14 days (gestation, daily)	Rat (male / female)	No effect	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	≥ 600 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 422	≥ 600 mg/kg bw/day		Rat (male / female)	No effect	Experimental value	

calcium carbonate

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (diet))	NOAEC	Equivalent to OECD 414	1963 mg/kg bw/day - 2188 mg/kg bw/day	62 day(s)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Oral (diet))	NOAEC	Equivalent to OECD 414	1963 mg/kg bw/day - 2188 mg/kg bw/day	62 day(s)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOEL	OECD 422	1000 mg/kg bw/day	48 day(s)	Rat (male / female)	No effect	Experimental value	

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

NAE-1600 B

Judgement is based on the relevant ingredients
Not classified for aspiration toxicity

Toxicity other effects

NAE-1600 B

No (test)data on the mixture available

Chronic effects from short and long-term exposure

NAE-1600 B

Skin rash/inflammation.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

NAE-1600 B

No (test)data on the mixture available
Judgement of the mixture is based on the relevant ingredients

NAE-1600 B

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	> 500 mg/l	96 h	Leuciscus idus	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	> 103 mg/l	48 h	Daphnia magna	Static system	Fresh water	Read-across; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	73 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; GLP
	NOEC	OECD 201	45 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; Growth rate
Toxicity aquatic micro-organisms	NOEC	Equivalent to OECD 209	580 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; Respiration

N,N'-bis(3-aminopropyl)ethylenediamine

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	DIN 38412-15	220 mg/l - 460 mg/l	96 h	Leuciscus idus	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	43 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 100 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	50 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity aquatic crustacea	NOEC	OECD 211	7.2 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC10	OECD 209	34 mg/l	180 minutes	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

3,3'-oxybis(ethyleneoxy)bis(propylamine)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	DIN 38412-15	215 mg/l - 464 mg/l	96 h	Leuciscus idus	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	218 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50	DIN 38412-9	> 500 mg/l	72 h	Scenedesmus subspicatus	Static system	Fresh water	Experimental value; Nominal concentration
	EC10	DIN 38412-9	5.4 mg/l	72 h	Scenedesmus subspicatus	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity fish	NOEC		> 1 mg/l		Leuciscus idus		Fresh water	Calculated value
Long-term toxicity aquatic crustacea	EC10		25 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR
Toxicity aquatic micro-organisms	EC50	DIN 38412-8	222 mg/l	17 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

NAE-1600 B

calcium carbonate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 %	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	> 100 %	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	50 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	Dose level		60 mg/l	42 day(s)	Oncorhynchus mykiss	Flow-through system	Fresh water	Experimental value; Calcium ion
Toxicity aquatic micro-organisms	EC50	OECD 209	> 1000 mg/l	3 h	Activated sludge			Literature study

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	69 % - 87 %; GLP	29 day(s)	Weight of evidence

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	94 h	1.5E6 /cm ³	Calculated value

N,N'-bis(3-aminopropyl)ethylenediamine

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	70 %; GLP	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	1.6 h	5E5 /cm ³	Calculated value

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	0 %; GLP	28 day(s)	Experimental value

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

NAE-1600 B

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

Log Kow

Method	Remark	Value	Temperature	Value determination
EU Method A.8		-0.96	50 °C	Experimental value

N,N'-bis(3-aminopropyl)ethylenediamine

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	Equivalent to OECD 305	< 5	6 week(s)	Cyprinus carpio	Read-across

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		-1.6	23 °C	Experimental value

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		-1.3	25 °C	Experimental value

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

12 / 18

NAE-1600 B

calcium carbonate

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (inorganic)			

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.58 - 1.2	Calculated value

N,N'-bis(3-aminopropyl)ethylenediamine

(log) Koc

Parameter	Method	Value	Value determination
log Koc	OECD 106	3.2 - 3.7	Experimental value

3,3'-oxybis(ethyleneoxy)bis(propylamine)

(log) Koc

Parameter	Method	Value	Value determination
log Koc		1.2	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

PMT conclusion

Does not contain component(s) that meet(s) the criteria of PMT and/or vPvM as listed in Annex I of Regulation (EC) No 1272/2008

NAE-1600 B

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

Water ecotoxicity pH

pH shift

N,N'-bis(3-aminopropyl)ethylenediamine

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

3,3'-oxybis(ethyleneoxy)bis(propylamine)

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

Water ecotoxicity pH

pH shift

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

13 / 18

NAE-1600 B

calcium carbonate

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number or ID number

UN number	2735
-----------	------

14.2. UN proper shipping name

Proper shipping name	amines, liquid, corrosive, n.o.s. (N,N'-bis(3-aminopropyl) ethylenediamine; 3,3'-oxybis(ethyleneoxy)bis(propylamine))
----------------------	---

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C7

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Rail (RID)

14.1. UN number or ID number

UN number	2735
-----------	------

14.2. UN proper shipping name

Proper shipping name	amines, liquid, corrosive, n.o.s. (N,N'-bis(3-aminopropyl) ethylenediamine; 3,3'-oxybis(ethyleneoxy)bis(propylamine))
----------------------	---

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C7

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Inland waterways (ADN)

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

14 / 18

NAE-1600 B

14.1. UN number or ID number	
UN number/ID number	2735
14.2. UN proper shipping name	
Proper shipping name	amines, liquid, corrosive, n.o.s. (N,N'-bis(3-aminopropyl) ethylenediamine; 3,3'-oxybis(ethyleneoxy)bis(propylamine))
14.3. Transport hazard class(es)	
Class	8
Classification code	C7
14.4. Packing group	
Packing group	II
Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Sea (IMDG/IMSBC)

14.1. UN number or ID number	
UN number	2735
14.2. UN proper shipping name	
Proper shipping name	amines, liquid, corrosive, n.o.s. (N,N'-bis(3-aminopropyl) ethylenediamine; 3,3'-oxybis(ethyleneoxy)bis(propylamine))
14.3. Transport hazard class(es)	
Class	8
14.4. Packing group	
Packing group	II
Labels	8
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable, based on available data

Air (ICAO-TI/IATA-DGR)

14.1. UN number or ID number	
UN number/ID number	2735
14.2. UN proper shipping name	
Proper shipping name	amines, liquid, corrosive, n.o.s. (N,N'-bis(3-aminopropyl) ethylenediamine; 3,3'-oxybis(ethyleneoxy)bis(propylamine))
14.3. Transport hazard class(es)	
Class	8
14.4. Packing group	
Packing group	II
Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A3
Special provisions	A803
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	0.5 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
23 % - 58 %	
333 g/l - 841 g/l	

Directive 2012/18/EU (Seveso III)

Not subject to registration according to Directive 2012/18/EU (Seveso III)

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

15 / 18

NAE-1600 B

REACH Candidate list

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> · N,N'-bis(3-aminopropyl)ethylenediamine · 3,3'-oxybis(ethyleneoxy)bis(propylamine) 	<p>Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>1. Shall not be used in:</p> <ul style="list-style-type: none"> — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none"> — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <ul style="list-style-type: none"> a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
<ul style="list-style-type: none"> · p-toluenesulphonic acid (containing a maximum of 5 % H2SO4) 	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p> <p>The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.</p>	<p>Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081</p>

National legislation Belgium

NAE-1600 B

No data available

National legislation The Netherlands

NAE-1600 B

Waterbezwaarlijkheid	B (3); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

16 / 18

NAE-1600 B

National legislation France

NAE-1600 B

No data available

National legislation Germany

NAE-1600 B

Lagerklasse (TRGS510)	8 A: Brennbare ätzende Gefahrstoffe
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
<u>p-toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)</u>	
TA-Luft	5.2.1
<u>N,N'-bis(3-aminopropyl)ethylenediamine</u>	
TA-Luft	5.2.5/I
<u>3,3'-oxybis(ethyleneoxy)bis(propylamine)</u>	
TA-Luft	5.2.5
<u>calcium carbonate</u>	
TA-Luft	5.2.1

National legislation Austria

NAE-1600 B

No data available

National legislation United Kingdom

NAE-1600 B

No data available

National legislation Ireland

NAE-1600 B

No data available

Other relevant data

NAE-1600 B

No data available

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
- H373 May cause damage to organs (kidneys, teeth) through prolonged or repeated exposure if swallowed.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ERC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
HS	Harmonized System of Nomenclature, a standardized international system for classifying goods under the Harmonized System Convention, as drawn up by the World Customs Organization Secretariat
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

17 / 18

NAE-1600 B

STP
vPvB

Sludge Treatment Process
very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2; 3; 6; 8; 9; 10; 11; 12; 14; 15

Publication date: 2022-03-08

Date of revision: 2025-12-26

Revision number: 0100

BIG number: 68033

18 / 18