SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

SHOCK SPRAY

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SHOCK SPRAY

Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Rust solvent

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*

Industrielaan 5B

B-2250 Olen

2 +32 14 25 76 40

⊞ +32 14 22 02 66

info@novatio.be

*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No. 1272/2008

stabilities as sangerous about and to the differia of Regulation (20) the 1272/2000				
Class	Category	zard statements		
Aerosol	category 1	: Extremely flammable aerosol.		
Aerosol	category 1	: Pressurised container: May burst if heated.		
Eye Irrit.	category 2	9: Causes serious eye irritation.		
STOT SE	category 3	36: May cause drowsiness or dizziness.		

2.2. Label elements





Contains: propan-2-ol.

Signai word	Danger
H-statements	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

P-statements

Technische Schoolstraat 43 A, B-2440 Geel

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210 P211 Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. P251

P280 Wear eye protection.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

http://www.big.be

© BIG vzw

Reason for revision: 9;11

Revision number: 0800

Publication date: 2001-05-16 Date of revision: 2022-06-23

BIG number: 32260

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

	CAS No EC No	Conc. (C)	Classification according to CLP	Note	lRemark	M-factors and ATE
propan-2-ol 01-2119457558-25		<c<60%< td=""><td>Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336</td><td>(1)(2)(10)</td><td>Constituent</td><td></td></c<60%<>	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
petroleum gases, liquefied		<c<60%< td=""><td>Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280</td><td>(1)(2)(10)</td><td>Propellant</td><td></td></c<60%<>	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	

⁽¹⁾ For H- and EUH-statements in full: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dizziness. Drowsiness.

After skin contact:

No effects known.

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher. Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

Reason for revision: 9;11 Publication date: 2001-05-16 Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 2/13

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight. Protect against frost.

7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m³
	Short time value	400 ppm
	Short time value	1000 mg/m³
Pétrole (gaz liquéfié)	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1826 mg/m³

The Netherlands

Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure	5 mg/m³
	limit value)	
	·	

France

Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m³

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 3 / 13

Germany

Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m ³

Austria

2-Propanol Kurzzeitwert für Großguss	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	2000 mg/m ³
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m ³

UK

Liquefied petroleum gas	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1000 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1750 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1250 ppm
	Short time value (Workplace exposure limit (EH40/2005))	2180 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m ³

USA (TLV-ACGIH)

2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

USA (BEI-ACGIH)

2-Propanol (Acetone) Urine: end of shift at end of workweek 40 mg/L Background, Nonspecific

8.1.2 Sampling methods

Product name	Test	Number
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	OSHA	109

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

DNEL/DMEL - General population

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

PNEC

propan-2-ol

Compartments	Value	Remark
Fresh water	140.9 mg/l	
Fresh water (intermittent releases)	140.9 mg/l	
Marine water	140.9 mg/l	
STP	2251 mg/l	
Fresh water sediment	552 mg/kg sediment dw	
Marine water sediment	552 mg/kg sediment dw	
Soil	28 mg/kg soil dw	
Oral	160 mg/kg food	

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 4 / 13

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Hydrocarbon odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	1.4 - 10.9 vol % ; Propellant
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	No data available in the literature
Boiling point	-40 °C2 °C ; Propellant
Relative vapour density	Not applicable (aerosol)
Vapour pressure	5900 hPa - 17600 hPa ; Propellant
Solubility	Water ; insoluble
Relative density	No data available in the literature
Absolute density	No data available in the literature
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
рН	Not applicable (non-soluble in water)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

Reason for revision: 9;11 Publication date: 2001-05-16

Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 5 / 13

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11 1 1 Tost results

Acute toxicity

SHOCK SPRAY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

SHOCK SPRAY

No (test)data on the mixture available

Classification is based on the relevant ingredients

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	l '	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

SHOCK SPRAY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Dermal	Not sensitizing	OECD 406		Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for skin $% \left\{ 1,2,...,n\right\}$

Not classified as sensitizing for inhalation

Specific target organ toxicity

SHOCK SPRAY

No (test)data on the mixture available

Classification is based on the relevant ingredients

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm			104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male / female)	Experimental value

Conclusion

May cause drowsiness or dizziness. Not classified for subchronic toxicity

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 6 / 13

Mutagenicity (in vitro)

SHOCK SPRAY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
activation, negative					
without metabolic					
activation					
Negative with metabolic	Equivalent to OECD 476	Chinese hamster ovary	No effect	Experimental value	
activation, negative		(CHO)			
without metabolic					
activation					

Mutagenicity (in vivo)

SHOCK SPRAY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD		Mouse (male / female)		Experimental value
	474				

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

SHOCK SPRAY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation	NOEL	OECD 451	5000 ppm	104 weeks (6h / day,	Rat (male /	No carcinogenic		Experimental value
(vapours)				5 days / week)	female)	effect		

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

SHOCK SPRAY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

SHOCK SPRAY

No (test)data on the mixture available

Chronic effects from short and long-term exposure

SHOCK SPRAY

Dry skin.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

Reason for revision: 9;11 Publication date: 2001-05-16

Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 7 / 13

SECTION 12: Ecological information

12.1. Toxicity

SHOCK SPRAY

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

propan-2-ol

<u>горан z ог</u>								
	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow- through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC		2344 μmol/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	17.668 h	1.5E6 /cm ³	Calculated value

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

SHOCK SPRAY

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

propan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
			25 °C	Weight of evidence approach

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

propan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	ISBC DCKOCWIN VO O	0.185 - 0.541	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 8 / 13

12.7. Other adverse effects

SHOCK SPRAY

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

propan-2-ol

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

14 06 03* (waste organic solvents, refrigerants and foam/aerosol propellants: other solvents and solvent mixtures). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road	(/	۱D	₹)
14.	1.	UN	nu

4. <u>1. UN number</u>	
UN number	1950
4.2. UN proper shipping name	
Proper shipping name	aerosols
4.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
4.4. Packing group	
Packing group	
Labels	2.1
4.5. Environmental hazards	
Environmentally hazardous substance mark	no
4. <u>6. Special precautions for user</u>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo
	liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

٠ ٠.	,	
14.	1. UN number	
	UN number	1950
14.	2. UN proper shipping name	
	Proper shipping name	aerosols
14.	3. Transport hazard class(es)	
	Hazard identification number	23
	Class	2
	Classification code	5F
14.	4. Packing group	
	Packing group	
	Labels	2.1
14.	5. Environmental hazards	
	Environmentally hazardous substance mark	no

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 9 / 13

4.6. Special precautions for user Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
d waterways (ADN)	
I.1. UN number	Lacro
UN number	1950
I.2. UN proper shipping name	la avance la
Proper shipping name	aerosols
.3. Transport hazard class(es)	
Class	2
Classification code	5F
I.4. Packing group	
Packing group	
Labels	2.1
5.5. Environmental hazards	
Environmentally hazardous substance mark	no
6.6. Special precautions for user	400
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
(IMDG/IMSBC)	
.1. UN number	
UN number	1950
.2. UN proper shipping name	
Proper shipping name	aerosols
.3. Transport hazard class(es)	
Class	2.1
.4. Packing group	
Packing group	
Labels	2.1
.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
.7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78	Not applicable
CAO-TI/IATA-DGR)	livor applicable
.1. UN number	
UN number	1950
-2. UN proper shipping name	
Proper shipping name	aerosols, flammable
i roke, suikking name	25.000.07.101.1110.00
3 Transport hazard class(es)	2.1
· · ·	L±
Class	
Class -4. Packing group	
Class 1.4. Packing group Packing group	21
Class 1.4. Packing group Packing group Labels	2.1
Class 1.4. Packing group Packing group Labels 1.5. Environmental hazards	
Class 1.4. Packing group Packing group Labels 1.5. Environmental hazards Environmentally hazardous substance mark	2.1 no
Class .4. Packing group Packing group Labels .5. Environmental hazards Environmentally hazardous substance mark .6. Special precautions for user	no
Class 1.4. Packing group Packing group Labels 1.5. Environmental hazards Environmentally hazardous substance mark 1.6. Special precautions for user Special provisions	no A145
4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user	no

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 10 / 13

Passenger and cargo transport

Limited quantities: maximum net quantity per packaging 30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
60 % - 100 %	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

		Top tier (tonnes)		For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

and use of certain	dangerous substances, mixtures and articles. Designation of the substance, of the group of	Conditions of restriction
	substances or of the mixture	conditions of restriction
propan-2-ol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even wit ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopte by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers sha ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibl and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legib and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibliand indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
propan-2-ol	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/20

Reason for revision: 9;11 Publication date: 2001-05-16

Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 11/13

classified due to effects only following exposure by inhalation - reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B - skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of

this entry.

National legislation Belgium

SHOCK SPRAY

No data available

propan-2-ol

 -Andlesses Basseltad
Livre VI, titre 2)
(Code du bien-être au travail,
mutagènes et reprotoxiques
Agents cancérigènes,

alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à l'acide fort dans la fabrication d'alcool isopropylique.

petroleum gases, liquefied

Additional classification

Pétrole (gaz liquéfié); C; La mention "C" signifie que l'agent en question relève du champ d'application de l'arrêté royal du 2 décembre 1993 concernant la protection des travailleurs contre les risques liés à l'exposition à des agents cancérigènes et mutagènes et reprotoxiques au travail.

National legislation The Netherlands

SHOCK SPRAY

Waterbezwaarlijkheid Z (2); Algemene Beoordelingsmethodiek (ABM)

National legislation France

SHOCK SPRAY

No data available

National legislation Germany

	<u>OUCK SPRAY</u>		
	WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
propan-2-ol			
	TA-Luft	5.2.5	
	TRGS900 - Risiko der	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen	
	Fruchtschädigung	Grenzwertes nicht befürchtet zu werden	

National legislation Austria

SHOCK SPRAY

No data available

National legislation United Kingdom

SHOCK SPRAY

No data available

Other relevant data

SHOCK SPRAY

No data available

propan-2-ol

-					
	IARC - classification	3; Isopropanol			
	TLV - Carcinogen	2-propanol: A4			

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 9;11 Publication date: 2001-05-16

Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 12 / 13

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE Acute Toxicity Estimate

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEC/NOAEL No Observed Adverse Effect Concentration/No Observed Adverse Effect Level

NOEC/NOEL No Observed Effect Concentration/No Observed Effect Level
OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 9;11 Publication date: 2001-05-16
Date of revision: 2022-06-23

Revision number: 0800 BIG number: 32260 13 / 13