



Pneumatic Tool Cleaner

CLEANS, LUBRICATES AND PROTECTS COMPRESSED AIR TOOLS AND INSTALLATIONS

- ✓ Suitable for all compressed air driven devices and equipment.
- ✓ Drives away moisture and cleans.
- ✓ Prevents catches and blocking.
- ✓ Increases the RPMs and gives a better yield.
- ✓ Guarantees a longer life span.

Technical Info

- Physical state 20°C: liquid.
- Odour: none.
- Boiling point: 187°C - 211°C.
- Vapour pressure at 20°C (hPa): 8530.
- Relative density 20°C: 0.808.
- Flash point: 67°C.
- Self ignition: 255°C.
- Solubility in water: non-soluble.
- Dynamic viscosity 20°C: 1 mPa.s.
- Kinematic viscosity 20°C: 1 mPa.s.
- Protection period: 1 - 6 months depending on the systems and use.
- Shelf life: 36 months, keep dry, cool and frostproof.
- Safety measures: consult the Safety Data Sheet.

Packing

Pneumatic Tool Cleaner - aerosol 600ml

236106000

Product [PTC]

Characteristics

- Has been specially developed to give pneumatic equipment a longer lifespan.
- Cleans all pneumatic equipment, with the result that these get blocked less quickly.
- Lubricates and protects the machine so that it has a better yield.
- Drives away moisture from pneumatic equipment and installations.

Applications

- Internal cleaning and lubrication of compressed air machines.
- Release jammed valves and moving parts.
- Drives moisture away from installations and equipment.
- Detaches dirt and dust, which means the internal mechanism will react more quickly.
- Prevents the deposition of lime.
- Lubricates roller bearings, ...
- Can be used with chipping hammers, spray guns, hammer drills, compressors, pressure switches, nailing machines, staplers, ratchet spanners, impact wrenches, drum pumps, pneumatic drills, sheet metal nibblers, sanders, ...

Use