



# Novatex Tape HM

TEXTILE TAPE WITH A VERY HIGH IMMEDIATE ADHESIVE POWER

- ✓ Very fast adhesiveness thanks to the Hot-melt glue.
- ✓ Fine, woven textile tape easy to tear, even lengthwise.
- ✓ Can be repositioned.
- ✓ Very good temperature resistance up to 70°C.
- ✓ Adheres to most surfaces.

## Technical Info

- Thickness of the tape: +/- 0.21 mm.
- Thickness of the glue: +/- 80 micron.
- Tensile strength: 6,5 kN/m test method GB 7753-87.
- Temperature resistance: -15°C to +70°C.
- Elasticity: 25%.
- Rolling Ball Tack: 4 test method GB 7125-84.
- Adhesiveness: > 12 hrs test method GB 4851-84.
- Colour: yellow.
- First test foundations based on PE, PP, silicones and bitumen for adhesion.
- Shelf life: 24 months, keep dry, cool and frost-proof.

## Packing

Novatex Tape HM yellow - roll 50mm / 50m

561038000

## Product

### Characteristics

- A fine woven textile tape provided with a strong Hot-melt glue, with a very high immediate adhesive power.
- Easy to tear, even lengthwise.

### Applications

- sealing of air ducts
- bundling of cables
- repair of port sails
- third hand fixing
- temporary fixings - stand construction
- sealing of air-conditioning ducts
- repair of exhaust systems
- fixing of plastic film for storage
- temporary sealing of window and door openings
- temporary repair of broken windows
- protection of sharp corners and sides
- indispensable in each company car
- can be used as marking tape in combination with black Novatex Tape

## Use