



Seal & Bond Special Primer Windows and Doors

Surface Protection & Treatment

RAPID ADHESIVE PRIMER FOR DIFFICULT MATERIALS

- ✓ For gluing, taping and painting.
- ✓ Transparent.
- ✓ Leaves no traces or marks.
- ✓ Quick and easy.

Technical Info

- Colour: transparent.
- Base: polyolefin.
- Consumption: $\pm 2\text{-}3 \text{ m}^2$ per 400 ml, $\pm 1\text{-}1/2 \text{ m}^2$ per 150 ml.
- Drying time: ± 10 min.
- VOC value: 276.4 g/l.
- Substrates: PP, PP/EPDM, ABS, SAN PC, PA, PUR-RIM, R-TRU, PPO, PBT, PUR flexible foam, up-GF plastic, powder coating, painted surfaces.
- SEAL & BOND SPECIAL PRIMER is 100% free of heavy metals.
- The aerosols are manufactured from recycled materials and contain only CFC-free propellants.
- Shelf life: 36 months at a temperature of 10 °C to 25 °C and max. humidity of 60%.
- Safety measures: please consult the safety data sheet.

Packing

Seal & Bond Special Primer Windows and Doors - aerosol 400ml

590922116

Product [SSP R&D]

Characteristics

Significantly increases adhesion to hard-to-treat materials such as powder coating, painted surfaces, PP, PP/EPDM, ABS, SAN PC, PA, PUR-RIM, RTRU, PPO, PBT, PUR flexible foam, UP-GF plastic, etc. .

Use

- Clean the substrate with Safety Clean and/or Multifoam.
- Rub or blow dry.
- After releasing the mixing ball, shake well before use.
- Apply in a thin layer and allow to dry for 10 minutes at 20 °C.
- Further processing (gluing, taping, painting). The perfect combination with Novatio Sealtrans. Turn over after use and spray gas to keep the nozzle clean. Does not add value to bare metals.