



XPR-90 Safe Remover

FOR REMOVAL OF HARDENED GREASE AND SILICONES, GLUE AND WAX

- ✓ Does not run or drip.
- ✓ Long working time.
- ✓ With powerful lime extracts.

Technical Info

- Composition: aliphatic hydrocarbon solvent, binder, and citrus extracts.
- Boiling point/boiling range °C: 130 - 166.
- Vapour pressure/20°C hPa: 4.6.
- Relative density/20°C: 0.75.
- Physical state/20°C: liquid.
- Flashpoint °C: 24.
- Self-combustion °C: 200.
- Water solubility: insoluble.
- Odour: distinctive.
- Dynamic viscosity mPa.s/20°C: 1.
- Kinematic viscosity, mm²/s/20°C: 1.
- Volatile organic compound (VOC) %: 100.
- Volatile organic compound (VOC) g/l: 710.
- For specific technical information per package, please consult the SDS and MSDS.

Packing

XPR-90 Safe Remover - aerosol 500ml

683840000

Product [SAR90]

Characteristics

Versatile cleaner in gel form, also suitable for vertical applications. An aliphatic hydrocarbon solvent with added lime extracts.

Applications

Safe to use on most materials to remove wax, glue, grease and silicone residues, even hardened ones.

Use

- Apply and allow to act according to pollution.
- Rub off the loosened soiling.
- If necessary, repeat the treatment.
- Always rinse the cleaned surface with clean water.