

# Anti Spat

THE PROTECTION AGAINST WELDING SPATTERS

- Prevents welding spatters from sticking onto base materials.
- Contains no silicones or solvents.
- Simplifies the maintenance of welding torches extends the life span.
- Simple: spray weld remove spatters with cloth or brush.
- Paintable.
- Contains anti-corrosion additives.
  - Unflammable non-toxic safe to use.

### **Technical Info**

- · Appearance (at 20°C): liquid.
- Odour: odourless.
- Colour: white.
- pH 6.5/7.5.
- Boiling point/boiling range: 100°C. Relative density (at 20°C): 0.9/1.0.
- Water solubility: miscible with water.
- Shelf life: 24 months, keep dry, cool and frostproof.
- Safety measures: consult the Safety Data Sheet.

### Packing

Anti Spat - aerosol 400ml

371011000

### Use

## Product [ASP]

### Characteristics

Anti Spat is a water-based anti-adhesion agent for welding spatters. Anti Spat contains no silicones or solvents, is fire-proof, odourless and biologically degradable. Due to its high content of surface active substances, Anti Spat is very economical in use. Anti Spat contains corrosion inhibitors to protect the surface. Anti Spat has no influence for post-treatment on the surface, e.g. painting.

### Applications

Is ideal to use with both autogeneous and arc welding in industry, car repair shops, ...

novatio